

Blind rivet - RVT-AL/ST 3,2/10 - 3240511

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Blind rivets, Ø 3.2 mm, 10 mm sleeve length, aluminum sleeve, zinc-plated steel pin, flat head, standard version similar to DIN 7337 A

Product Features

- Special rivets are available for fixing RW... and UW... high-current panel feed-through terminal blocks that are specifically designed for terminal blocks
- Compact, ergonomically shaped pliers
- 3 inserts for rivet diameter of 2.4 - 3.2 mm, 4 mm, and 4.8 - 5.0 mm



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	500 pc
Weight per Piece (excluding packing)	1.08 g
Custom tariff number	83082000
Country of origin	China

Technical data

Dimensions

Length (b)	10 mm
Hole diameter	3.3 mm
Diameter	3.2 mm

General

Color	silver
Material	Aluminum (AlMg 3/3.5)/galvanized steel

Blind rivet - RVT-AL/ST 3,2/10 - 3240511

Classifications

eCl@ss

eCl@ss 4.0	21043074
eCl@ss 4.1	21043074
eCl@ss 5.0	23120402
eCl@ss 5.1	23120402
eCl@ss 6.0	23120402
eCl@ss 7.0	23120402
eCl@ss 8.0	23120402

ETIM

ETIM 3.0	EC002339
ETIM 4.0	EC002339
ETIM 5.0	EC002339

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

Accessories

Accessories

Riveting tools

Replacement clamping part - UNIFOX-RVT M/BIT 2,4L - 1212477



Nosepiece, specially designed for RVT-AL/ST 2,4L/... rivets, for fixing UW/RW/PW 4...

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

3240511