

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT 1997 ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	-			G10 ECR-15-001276	29JAN2015	GSK	MKO
				G11 ECR-16-016696	11SEP2017	GR	MKO
				G12 ECR-16-016780	15NOV2017	GR	MKO
				G13 ECR-17-014011	27MAR2018	SG	MKO

NOTES

- PARTS SHALL BE FREE AND CLEAN OF SHARP EDGES AND ALL OTHER FOREIGN MATERIAL NO LOOSE BURRS PERMITTED.
- NBR, 70°±5° SHORE A, BLACK, ACC .TO DIN 3770
- FKM, 70°±5° SHORE A, TEMPERATURE RANGE -30 °C / +200 °C
- EPDM, 65°±5° SHORE A, BLACK, ELECTRICAL CONDUCTIVE, RESISTIVITY: 8.05 x 10³ OHMS PER CM
- PACKAGING PN 0-1, 1000 PIECES MAX. IN A BOX

PART NO	A	B	NBR	FKM	EPDM COND	SERIES	NOTE
9-9	28.0	2.5	X	-	-	EMV-K3/4	-
9-4	3.5	1	X	-	-	AIR	-
9-3	4.5	1.5	X	-	-	AIR	OBSOLETE
9-2	47.7	3.5	X	-	-	AM-3P	-
9-1	11.0	1.0	X	-	-	AM-1P	-
8-2	54.0	3.0	X	-	-	AM-3P	-
8-1	50.0	3.0	X	-	-	AS-1P	-
7-6	168.0	3.0	X	-	-	AM-4P	-
7-2	50.0	2.0	-	X	-	Pg42	OBSOLETE
7-1	50.0	2.0	X	-	-	Pg42	-
6-6	135.0	3.0	X	-	-	AM-4P	OBSOLETE
6-2	44.0	2.0	-	X	-	Pg36	OBSOLETE
6-1	44.0	2.0	X	-	-	Pg36	OBSOLETE
5-6	5.0	1.0	X	-	-	MDC	-
5-3	7.0	3.0	X	-	-	AG-M6	-
5-2	34.0	2.0	-	X	-	Pg29	COLOR GREY
5-1	34.0	2.0	X	-	-	Pg29	OBSOLETE
4-6	12.5	2.5	X	-	-	MDC	-
4-4	98.0	3.0	-	-	X	HP/EMV 2#	OBSOLETE
4-3	98.0	3.0	X	-	-	ABB-S0	-
4-2	26.0	2.0	-	X	-	Pg21	-
4-1	26.0	2.0	X	-	-	Pg21	-
3-6	24.0	3.0	X	-	-	MDC	-
3-5	64.0	3.0	X	-	-	AH-1P	-
3-4	80.0	3.0	-	-	X	HP/EMV 16	OBSOLETE
3-3	80.0	3.0	X	-	-	AK-1P	-
3-2	20.0	1.5	-	X	-	Pg16	COLOR GREY
3-1	20.0	1.5	X	-	-	Pg16	-
2-6	250.0	3.0	X	-	-	MDC	-
2-5	38.0	3.0	X	-	-	AH-1P	OBSOLETE
2-4	67.0	2.8	-	-	X	HP/EMV10	-
2-3	67.0	2.8	X	-	-	HP/EMV10	-
2-2	18.0	1.5	-	X	-	Pg13.5	OBSOLETE
2-1	18.0	1.5	X	-	-	Pg13.5	OBSOLETE
1-9	20.0	1.25	-	X	-	HC 26	BLACK (G9)
1-8	20.0	1.0	-	X	-	HC 26	BLACK OBSOLETE
1-7	4.0	1.0	-	X	-	ARRI	-
1-6	330	5.0	X	-	-	MDC	-
1-5	19.0	1.8	X	-	-	Pg-Stv	OBSOLETE
1-4	59.0	3.0	-	-	X	HP/EMV6	OBSOLETE
1-3	59.0	3.0	X	-	-	HP/EMV6	-
1-2	16.0	1.5	-	X	-	Pg11	OBSOLETE
1-1	16.0	1.5	X	-	-	Pg11	-
1-0	23.0	1.0	-	X	-	HC26	COLOR BLUE OBSOLETE
0-9	23.52	1.78	-	X	-	HC25	-
0-8	26	1.5	-	X	-	HC26	COLOR BLUE OBSOLETE
0-7	40	2.5	X	-	-	HW-G	OBSOLETE
0-6	25.0	1.5	X	-	-	ALM	COLOR BLACK
0-5	17.5	1.5	-	X	-	HC20	COLOR BLUE
0-4	17	1.0	-	X	-	HC20	COLOR BLUE
0-3	21.2	2.65	-	X	-	HF-1-EMV-K	-
0-2	3.0	1.0	X	-	-	HA-EMV-K	-
0-1	13.0	1.5	X	-	-	Pg 09	-

A-A

SCALE 2:1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Rösigen 26.05.1999	TE Connectivity	
		CHK Schweiger 26.05.1999		
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ±		NAME: O-Ring PRODUCT SPEC: - APPLICATION SPEC: - WEIGHT: -
MATERIAL: -		SIZE: A2 CAGE CODE: 00779 DRAWING NO: C-1106053		RESTRICTED TO: - SCALE: 4:1 SHEET: 1 OF 1 REV: G13
CUSTOMER DRAWING				

1471-9 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-1106053-1](#)