

Socket terminal block - JBC 2,5/5 - 3240165

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



5-pos. socket terminal block with spring-cage connection, for toolless wiring with push-in connection method, for one and multi-strand conductors with a cross section of 0.5 to 2.5 mm², insulation housing transparent.

Product Features

- Different cross sections can be wired together in a junction box connector
- Thanks to Push-in connection technology, the three junction box connector versions from Phoenix Contact enable tool-free wiring in a small amount of space
- Solid single-strand conductors with a cross section range of 0.5 mm² to 2.5 mm² can be connected
- Solid multi-strand conductors (7 litz wires) with a cross section range of 1.5 mm² to 2.5 mm² can be safely connected
- The transparent housing makes it easier to carry out a visual inspection of the terminal points, thereby increasing wiring safety
- Integrated test openings enable the use of test devices once wiring has been completed



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	2.2 g
Custom tariff number	85369010
Country of origin	Austria

Technical data

General

Number of levels	1
Number of connections	5
Nominal cross section	2.5 mm ²
Color	transparent
Insulating material	PC/PA
Flammability rating according to UL 94	V2
Ambient temperature (operation)	90 °C

Socket terminal block - JBC 2,5/5 - 3240165

Technical data

General

Maximum load current	24 A
Nominal current I_N	24 A
Nominal voltage U_N	450 V

Dimensions

Width	26 mm
Length	15.6 mm
Height	8.9 mm
Depth	15.60 mm

Connection data

Connection method	Push-in connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	14
Conductor cross section flexible min.	1.5 mm ²
Conductor cross section flexible max.	2.5 mm ²
Min. AWG conductor cross section, flexible	16
Max. AWG conductor cross section, flexible	14
Stripping length	8 mm

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	27141104
eCl@ss 4.1	27141104
eCl@ss 5.0	27141104
eCl@ss 5.1	27141104
eCl@ss 6.0	27141106
eCl@ss 7.0	27141106
eCl@ss 8.0	27141120

ETIM

ETIM 3.0	EC001284
ETIM 4.0	EC001284

Socket terminal block - JBC 2,5/5 - 3240165

Classifications

ETIM

ETIM 5.0	EC000446
----------	----------

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

Approvals

Approvals

Approvals

UL Listed / EAC / EAC

Ex Approvals

Approvals submitted

Approval details

UL Listed 	
mm ² /AWG/kcmil	20-16
Nominal current IN	20 A
Nominal voltage UN	600 V

EAC

EAC

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[3240165](#)