

Specification Sheet

Part Number: T50L9C2



Cable Tie, 15" Long, UL Rated, 50lb Tensile Strength, PA66, Natural, 100/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 112-05419                                                                                                                                                                                                                                                                                                                                                                          |
| Type                | T50L                                                                                                                                                                                                                                                                                                                                                                               |
| Color               | Natural (NA)                                                                                                                                                                                                                                                                                                                                                                       |
| Features & Benefits | <ul style="list-style-type: none"><li>• Engineered and manufactured for maximum performance and quality.</li><li>• Made from 100% high-quality plastic to ensure efficient recycling.</li><li>• Inside serration for a strong grip onto bundles.</li><li>• Easy application either manually or with a tensioning tool.</li><li>• Bent tail allows for simpler insertion.</li></ul> |
| Quantity Per        | bag                                                                                                                                                                                                                                                                                                                                                                                |

|                                            |                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b>                 | T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| <b>Short Description</b>                   | Cable Tie, 15" Long, UL Rated, 50lb Tensile Strength, PA66, Natural, 100/pkg                                                                                                                                                                                                                                                                                 |
| <b>Global Part Name</b>                    | T50L-PA66-NA                                                                                                                                                                                                                                                                                                                                                 |
| <b>Minimum Tensile Strength (Imperial)</b> | 50.0                                                                                                                                                                                                                                                                                                                                                         |
| <b>Minimum Tensile Strength (Metric)</b>   | 225.0                                                                                                                                                                                                                                                                                                                                                        |
| <b>Length L (Imperial)</b>                 | 15.0                                                                                                                                                                                                                                                                                                                                                         |
| <b>Length L (Metric)</b>                   | 390.0                                                                                                                                                                                                                                                                                                                                                        |
| <b>Identification Plate Position</b>       | none                                                                                                                                                                                                                                                                                                                                                         |
| <b>Releasable Closure</b>                  | No                                                                                                                                                                                                                                                                                                                                                           |
| <b>Tie Closure</b>                         | plastic pawl                                                                                                                                                                                                                                                                                                                                                 |
| <b>Variant</b>                             | Inside Serrated                                                                                                                                                                                                                                                                                                                                              |
| <b>Width W (Imperial)</b>                  | 0.19                                                                                                                                                                                                                                                                                                                                                         |
| <b>Width W (Metric)</b>                    | 4.8                                                                                                                                                                                                                                                                                                                                                          |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06                                                                                                                                                                                                                                                                                                                                                         |

|                                        |                                                                                                |
|----------------------------------------|------------------------------------------------------------------------------------------------|
| <b>Bundle Diameter Min (Metric)</b>    | 1.5                                                                                            |
| <b>Bundle Diameter Max (Imperial)</b>  | 4.33                                                                                           |
| <b>Bundle Diameter Max (Metric)</b>    | 110.0                                                                                          |
| <b>Thickness T (Imperial)</b>          | 0.05                                                                                           |
| <b>Thickness T (Metric)</b>            | 1.2                                                                                            |
| <b>Material</b>                        | Polyamide 6.6 (PA66)                                                                           |
| <b>Material Shortcut</b>               | PA66                                                                                           |
| <b>US MIL SPEC</b>                     | SAE-AS33671<br>MS3367-2-9, Class 1                                                             |
| <b>Flammability</b>                    | UL 94 V2                                                                                       |
| <b>Halogen free</b>                    | Yes                                                                                            |
| <b>Operating Temperature (Metric)</b>  | -40°F to +185°F (-40°C to +85°C)                                                               |
| <b>Reach Complaint(Article 33)</b>     | Yes                                                                                            |
| <b>ROHS Complaint</b>                  | Yes                                                                                            |
| <b>Certification/Specification WEB</b> | CAGE Code 53421 BACS38K Bundesamt für Wehrtechnik   VG<br>95387 Part 4 Edition: 2008-12 MS3367 |

|                           |     |
|---------------------------|-----|
| <b>UL Recognized (US)</b> | Yes |
|---------------------------|-----|

|                                  |     |
|----------------------------------|-----|
| <b>UL Listed (US and Canada)</b> | Yes |
|----------------------------------|-----|

|                                      |     |
|--------------------------------------|-----|
| <b>UL Recognized (US and Canada)</b> | Yes |
|--------------------------------------|-----|

|                      |     |
|----------------------|-----|
| <b>UL Listed (US</b> | Yes |
|----------------------|-----|

|                                   |     |
|-----------------------------------|-----|
| <b>Package Quantity(Imperial)</b> | 100 |
|-----------------------------------|-----|

|                                  |     |
|----------------------------------|-----|
| <b>Package Quantity (Metric)</b> | 100 |
|----------------------------------|-----|

|                       |            |
|-----------------------|------------|
| <b>Customs Number</b> | 3926909988 |
|-----------------------|------------|

|                             |      |
|-----------------------------|------|
| <b>Content Unit(BMEcat)</b> | pcs. |
|-----------------------------|------|

|                        |     |
|------------------------|-----|
| <b>Weight (Metric)</b> | 2.7 |
|------------------------|-----|