

## Sensor/actuator cable - SAC-4P-MS/ 2,0-186 SCO - 1555606

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/actuator cable, 4-position, PUR, black-gray RAL 7021, Plug straight M12 SPEEDCON, A-coded, on free cable end, cable length: 2 m

### Your advantages

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ Save time, thanks to installation with SPEEDCON fast locking system
- ✓ High-performance: connectors and cables with a large conductor cross section for power supply



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 173506 |
| GTIN         | 4046356173506                                                                                           |

### Technical data

#### Dimensions

|                                            |       |
|--------------------------------------------|-------|
| Length of cable                            | 2 m   |
| Stripping length of the free conductor end | 50 mm |

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |

#### General

|                       |          |
|-----------------------|----------|
| Rated current at 40°C | 4 A      |
| Rated voltage         | 250 V AC |
|                       | 250 V DC |
| Number of positions   | 4        |
| Insulation resistance | ≥ 100 MΩ |

# Sensor/actuator cable - SAC-4P-MS/ 2,0-186 SCO - 1555606

## Technical data

### General

|                              |              |
|------------------------------|--------------|
| Coding                       | A - standard |
| Status display               | No           |
| Protective circuit/component | unwired      |
| Overvoltage category         | II           |
| Degree of pollution          | 3            |
| Insertion/withdrawal cycles  | ≥ 100        |
| Torque                       | 0.4 Nm       |

### Material

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | HB |
|----------------------------------------|----|

### Cable

|                                               |                                |
|-----------------------------------------------|--------------------------------|
| Cable type                                    | PUR POWER 0.75 mm² black       |
| Cable type (abbreviation)                     | 186                            |
| Cable abbreviation                            | LiY11Y                         |
| UL AWM style                                  | 20549 / 1061 (80°C/300 V)      |
| Conductor cross section                       | 4x 0.75 mm² (power line)       |
| AWG signal line                               | 18                             |
| Conductor structure signal line               | 42x 0.15 mm                    |
| Core diameter including insulation            | 1.75 mm ±0.05 mm               |
| Thickness, insulation                         | ≥ 0.23 mm (Core insulation)    |
|                                               | ≥ 0.76 mm (Outer cable sheath) |
| Wire colors                                   | brown, white, blue, black      |
| Overall twist                                 | 4 wires, twisted               |
| External sheath, color                        | black-gray RAL 7021            |
| External cable diameter D                     | 5.9 mm ±0.15 mm                |
| Smallest bending radius, movable installation | 59 mm                          |
| Minimum bending radius, fixed installation    | 5 x D                          |
| Minimum bending radius, flexible installation | 10 x D                         |
| Number of bending cycles                      | 2000000                        |
| Bending radius                                | 59 mm                          |
| Traversing path                               | 5 m                            |
| Traversing rate                               | 3 m/s                          |
| Acceleration                                  | 5 m/s²                         |

## Sensor/actuator cable - SAC-4P-MS/ 2,0-186 SCO - 1555606

### Technical data

#### Cable


|                                 |                                                     |
|---------------------------------|-----------------------------------------------------|
| Cable weight                    | 57 kg/km                                            |
| Outer sheath, material          | PUR                                                 |
| Material conductor insulation   | PVC                                                 |
| Conductor material              | Bare Cu litz wires                                  |
| Insulation resistance           | $\geq 1 \text{ M}\Omega \cdot \text{km}$ (at 20 °C) |
| Conductor resistance            | max. 26 $\Omega/\text{km}$ (at 20 °C)               |
| Nominal voltage, cable          | $\leq 300 \text{ V}$                                |
| Test voltage, cable             | $\geq 3000 \text{ V}$                               |
| Flame resistance                | according to UL 758/1581 (horizontal)               |
|                                 | in accordance with UL 758/1581 FT2                  |
| Resistance to oil               | According to DIN EN 60811-2-1, 168 h at 100°C       |
| Other resistance                | hydrolysis and microbe resistant                    |
|                                 | Low adhesion                                        |
|                                 | abrasion-resistant                                  |
|                                 | Resistant to salt water                             |
| Ambient temperature (operation) | -25 °C ... 80 °C (cable, fixed installation)        |
|                                 | -5 °C ... 80 °C (cable, flexible installation)      |

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |


### Drawings

Schematic diagram



Pin assignment M12 plug, 4-pos., A-coded, view plug side


Cable cross section




PUR POWER 0.75 mm² black [186]

Sensor/actuator cable - SAC-4P-MS/ 2,0-186 SCO - 1555606

Dimensional drawing



Circuit diagram



M12 SPEEDCON plug, straight

Contact assignment of the M12 plug

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed

Ex Approvals

Approval details

|                    |                                                                                     |                                                                                                                                                       |               |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 221474 |
| Nominal voltage UN |                                                                                     | 300 V                                                                                                                                                 |               |
| Nominal current IN |                                                                                     | 4 A                                                                                                                                                   |               |

|                    |                                                                                     |                                                                                                                                                       |               |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Listed         |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 221474 |
| Nominal voltage UN |                                                                                     | 300 V                                                                                                                                                 |               |
| Nominal current IN |                                                                                     | 4 A                                                                                                                                                   |               |

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.AI30.B.00767 |
|-----|-------------------------------------------------------------------------------------|--------------------------|

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| cULus Listed |  |
|--------------|-------------------------------------------------------------------------------------|

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>