



Part Number: 83004

Lead Wire, #24 Str SPC, TFE Ins, AWM 1213 105C TYPE E

Request Sample

Product Description

High Temp Plastic Lead Wire, 24AWG (7x32) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
24	7x32	SCC - Silver-coated Copp	per 1
Condu	ictor Count:	1	
Condu	ıctor Size:	2	4 AWG

Insulation

I	Material	Nominal Diameter	Nominal Wall Thickness
ľ	TFE - Tetrafluoroethylene	0.044 in	0.01 in

Outer Jacket Material



Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
24 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	10 amps

Voltage

Description	Voltage Rating [V]
Mil-W-16878/4	600 V

Temperature Range

Non-UL Temp Rating:	200°C
UL Temp Rating:	105°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

Bulk Cable Weight:	2 lbs/1000ft

Standards

UL AWM Style:	1213
Military Specification:	NEMA HP3, MIL-W-16878/4

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1	
UL voltage rating:	600 V RMS	

Plenum/Non-Plenum

Part Number

Variants

Item #	Color	Footnote
83004 010100	Black	E
83004 0101000	Black	ES
83004 006100	Blue, Light	E
83004 0061000	Blue, Light	ES
83004 001100	Brown	E
83004 0011000	Brown	ES
83004 008100	Gray	E
83004 0081000	Gray	ES
83004 005100	Green, Dark	E
83004 0051000	Green, Dark	ES
83004 003100	Orange	E
83004 0031000	Orange	ES
83004 002100	Red	E
83004 0021000	Red	ES
83004 007100	Violet	E
83004 0071000	Violet	ES
83004 009100	White	E
83004 0091000	White	ES
83004 004100	Yellow	E
83004 0041000	Yellow	ES

Foo	tnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.	
Foo	tnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)	

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.