

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2009

© COPYRIGHT 2009

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	BA1	ECR-14-010250	16JUL2014	KR	TN

1 TERMINAL WRAPAROUND APPROX 0.007" (0.18mm) BOTH ENDS
 2 FOR FURTHER INFORMATION SEE DATA SHEET FOR 3650 SERIES-LOW INDUCTANCE, HIGH FREQUENCY CHIP INDUCTOR

2.79
2.92

2.13
0.51
1.52
0.51

RECOMMENDED LAND PATTERN FOR 3650-2C SERIES

2.54
1.02
1.27
1.02

MAGNET WIRE
ELECTRODE (Ag/Pd+Ni+Sn)
CERAMIC CORE
UV GLUE

A-A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN SUBHASH.M 04-AUG-09

CHK ALLAN.P 04-AUG-09

APVD STEPHEN.P 04-AUG-09

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

Customer Drawing

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±0.2

1 PLC ±0.1

2 PLC ±

3 PLC ±

4 PLC ±

ANGLES ±5°

MATERIAL

FINISH

TE Connectivity

NAME
LOW INDUCTANCE, HIGH FREQUENCY
CHIP INDUCTOR SERIES 3650 2C

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1879023	-

SCALE	SHEET	OF	REV
NTS	1	1	BA1

ROHS Compliant

1470-19 (3/13)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[36502CR75JTDG](#)