

T18R2C2

Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66, Red, 100/pkg

Article Number: 111-01880

Part Number: T18R2C2

Type: T18R



→ [Find a Distributor](#)

→ [Order Samples](#)


→ [Get Technical Drawings](#)

    |  Share

→ **Base Data**

Part No.	T18R2C2
Type	T18R
Color	Red (RD)
Features	• Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple application by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

→ **Product Dimensions**



Min. Tensile Strength	18.0lbs / 80.0N
Length (L)	4.0" / 100.0mm
Width (W) (imperial)	0.1"
Width (W)	2.45mm
Min. Ø Bundle	0.06" / 1.5mm
Max. Ø Bundle	0.86" / 22.0mm

→ **Material and Specifications**

Material	Polyamide 6.6 (PA66)
----------	----------------------

- ▼ Cable Ties
 - 18-30 lb Tensile Strength**
 - 40-50 lb Tensile Strength
 - Heavy Duty Strength
 - Heavy Duty Wide Strap
 - Q Ties
 - Releasable
 - Releasable Heavy Duty
 - Clamp Ties
 - Double Head
 - Identification
 - Outside Serrated
 - Stainless Steel - 304
 - Stainless Steel - 316
 - High Temp Applications
 - Automatic Tool Cable Ties
 - Swivel Clip Cable Tie
 - Wire Harness Branch Ties
 - Aerial Support Spacer Ties
 - Releasable Grip Ties
- Cable Ties with Fasteners
- Cable Tie Tools
- Clamps and Clips
 - Heatshrink Moulded Shapes
- Mounts
- Heavy Duty Mounts
- Wire Connectors
- Wiring Duct
- Wiring Protection
- Labels, Printers and Software
 - Pre-Terminated Networking
- Copper Network Solutions
- Fiber Network Solutions
- Jacks and Wall Plates
- Racks - Cable Management
- Surface Raceway Systems

US MILSPEC	MS3367-4-2
CSA Certified	No
Flammability	UL94 V2
Material Specification	RoHS / HF
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	
Specification	UL ZODZ2.E64139 / MIL 53421
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes

 Logistic and Packaging

Packaging Type	bag
Pkg. Qty.	100
Carton Qty.	10000
EAN code	4031026274539
UPC	089306068372

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)