

~70

Ø20

M12x1

SW 18mm

SW 16mm

SW 13mm

PIN ARRANGEMENT

B-CODING

3-2271113-2	4-2271113-2

3-2 AS SHOWN
WIE GEZEICHNET

5-8	18 / 0.75mm ²		5	4-2271113-2
5-8	18 / 0.75mm ²		4	3-2271113-2
CABLE FEED-THROUGH mm	WIRES AWG / mm ²	MATERIAL	NUMBER OF POLES	TE-PART-NO.

DIESE ZEICHNUNG IST EIN KONTROLLIERTES DOKUMENT.
BEMASSUNGEN UND TOLERANZEN GEMAESS GPS (ISO STANDARDS).

THIS DRAWING IS A CONTROLLED DOCUMENT.
DIMENSIONING AND TOLERANCING PER GPS (ISO STANDARDS).

DIMENSIONS: MASSEINHEITEN: [mm]	TOLERANCES UNLESS OTHERWISE SPECIFIED: ALLGEMEINTOLERANZEN
	0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES/WINKEL ± FINISH/OBERFLÄCHE/FARBE

MATERIAL	-
	-

DWN YASHKUMAR 17MAY2014
CHK M.STRELOW 17MAY2014
APVD C.SCHREITLINGER 17MAY2014

PRODUCT SPEC
PRODUKTSPEZ.
-
APPLICATION SPEC
VERARBEITUNGSSPEZ.
-
WEIGHT
GEWICHT
-
Customer Drawing

NAME
M12 MALE STRAIGHT, FIELD INSTALLABLE
SHIELDED CONNECTOR, B-CODING
SCREW TERMINALS

SIZE
A2

CAGE CODE
00779

DRAWING NO
ZEICHNUNGS-NR.
C-2271113

RESTRICTED TO
NUR FÜR
-

TE Connectivity

SCALE
MASSSTAB
2:1

SHEET
BLATT
1 OF 1

REV
A2

1471-9 (3/13)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-2271113-2](#)