


REV. 0  
DCO 143832

COIL: @ 25°C  
RESISTANCE 880 OHMS ±10%  
NOMINAL VOLTAGE 18.0 VDC  
MUST OPERATE 10.6 VDC  
MUST RELEASE 6.0 VDC MAX, 0.91 VDC MIN.

ENVIRONMENT:  
VIBRATION 10 Hz TO 3000 Hz @ 30 g's  
SHOCK 75 g's 6 MS. DURATION  
TEMPERATURE -65 °C TO +125 °C  
NOTES: OPERATE TIME 2.0 MS MAX  
RELEASE TIME 4.0 MS MAX  
CONTACT BOUNCE 1.5 MS MAX.

## CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO  
1A 28 VDC RESISTIVE 100,000 OPERATIONS

DR. ASB 14NOV03

CR. ERRA 11/13/03

**CII Technologies**  
advanced control electronic solutions

CUST. QPL  
CUST. NO. M39016/15-104L REV.

"JMACD" RELAY

JMACD-18XLS

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMACD-18XLS](#) [1617122-6](#)