| SPECIFICATION CONTROL DRAWING | | | | | | | 55PC0241 | | |
|--|--|--|---|---|--|---|---|--|--|
| TITLE FOUR CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT | | | | | | Date | 10-22-05 | Revision | |
| | This sp | ecification sheet | forms a part of t | he latest issue | of Raychem Speci | fiction 55PC. | | | |
| | COMPONENT WIRES | 5 - 55PC0211 | | | | | | | |
| | | | CONSTR | UCTION DETAI | IS | | | 7 | |
| | | CONDUCTOR | DIAMETER (in.) | | | WEIGHT (Ibs/1000 ft.) | | | |
| | PART NUMBER <u>1</u> / | SIZE (AWG) | LOWER SPEC LIMIT | TARGET VALUE | UPPER SPEC LIMIT | TARGET VALUE | UPPER SPEC | | |
| | 55PC0241-24-* | 24 | .087 | .102 | .117 | 8.06 | 8.38 | | |
| | 55PC0241-22-* | 22 | .100 | .117 | .134 | 11.80 | 12.19 | _ | |
| | 55PC0241-20-* 55PC0241-18-* | 20 18 | .119 .139 | .139 .163 | .159 .188 | <u>17.83</u> 26.83 | 18.32 27.56 | _ | |
| | 55PC0241-16-* | 16 | .155 | .182 | .209 | 34.07 | 34.92 | - | |
| | 55PC0241-14-* | 14 | .189 | .221 | .253 | 52.44 | 53.64 | - | |
| | 55PC0241-12-* | 12 | .231 | .270 | .309 | 80.33 | 81.99 | | |
| | 55PC0241-10-* | 10 | .283 | .331 | .379 | 126.67 | 129.46 | | |
| | TEMPERATURE RATI Maximum continuous VOLTAGE RATING: INSULATION FLAWS Impulse Dielectric Te | NG: 150°C conductor temp 600 volts (rms) a | erature | PAR The a co com refle | REQUIREMENTS "*" in the part nur blor code designat ponent wire color ect the sequence Example: AWG 22 compone | or with a slash s. Colors show of manufacturir , black, red, ora | separating the n do not neces ig. | ssarily | |
| Tyco El | Users should evaluate the suit lectronics also reserves the right to mal | ability of this produ te changes in mate | ct for their application | on. Specifications which do not affe | s are subject to chan ct compliance with a | ge without notice. ny specification, v | vithout notification | n to Buyer. | |
| <u>1</u> / CC AN | DLORS AND COLOR CODE DESIGNATORS S ALTERNATIVE COLOR CODE MAY REPLAC IFFIXES MAY BE ADDED TO THE PART NUM | HALL BE IN ACCORD E MIL-STD-681 COLO | ANCE WITH MIL-STD- R CODE DESIGNATOR | 681. HOWEVER, DU RS. (EXAMPLE: "901 | JE TO LENGTH LIMITAT /902" MAY BE REPLA | IONS OF THE RAYC CED BY "Axxx".) OTH | HEM PART NUMBE | | |
| Page 1 of 1 | DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL | | | | | | t | Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 | |
| | THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID. | | | | | | Ele | Phone: 1-80-227-8816 Pctronics Fax: 1-650-361-6297 | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

<u>55PC0241-16-2/4/5/6CS2970</u> <u>55PC0241-22-ST4CS2666</u> <u>55PC0241-16-2/4/5/6CS2502</u> <u>55PC0241-20-</u> <u>2/4/5/6CS2502</u> <u>55PC0241-20-9/93/95/96</u> <u>55PC0241-22-2/4/5/6CS2970</u> <u>55PC0241-16-3/5/6/9</u> <u>55PC0241-20-</u> <u>2/4/5/6CS2970</u> <u>55PC0241-12-2/4/5/6CS2502</u> <u>55PC0241-22-2/4/5/6CS2502</u> <u>55PC0241-22-3/5/6/9</u> <u>55PC0241-16-</u> <u>9/93/95/96</u>