


LXP2-D

~14° diffused spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.7 mm
Fastening	tape
ROHS compliant	yes 


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LXP2-D	Single lens	PMMA		
LXP2-LH1-TAPE-BLK	Holder	PC		
HEIDI-TAPE	Tape	PU tape		

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA11482_LXP2-D	Single lens	1680	336	112	9.4
» Box size: 480 x 280 x 300 mm					







PHOTOMETRIC DATA (MEASURED):

CREE

LED XP-E
FWHM 14.0°
Efficiency 92 %
Peak intensity cd/lm
LEDs/each optic 1
Light colour White
Required components:

CREE

LED XP-E2
FWHM 10.0°
Efficiency 89 %
Peak intensity 21.400 cd/lm
LEDs/each optic 1
Light colour White
Required components:




CREE

LED XP-G
FWHM 16.0°
Efficiency 94 %
Peak intensity cd/lm
LEDs/each optic 1
Light colour White
Required components:

CREE



LED XP-G2
FWHM 13.0°
Efficiency 90 %
Peak intensity 11.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED XP-G3
FWHM 14.0°
Efficiency 88 %
Peak intensity 9.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XP-L HI
FWHM 12.0°
Efficiency 88 %
Peak intensity 13.000 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XT-E
FWHM 11.0°
Efficiency 88 %
Peak intensity 8.950 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED H35B0 (LEMWA32)
FWHM 11.0°
Efficiency 92 %
Peak intensity 15.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



LG Innotek

LED H35C0 (LEMWA33)
FWHM 13.0°
Efficiency 91 %
Peak intensity 10.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LG Innotek

LED H35C1 (LEMWA33)
FWHM 14.0°
Efficiency 88 %
Peak intensity 11.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON Q
FWHM 12.0°
Efficiency 89 %
Peak intensity 11.500 cd/lm
LEDs/each optic 1
Light colour White
Required components:



NICHIA

LED NVSW219D
FWHM 14.0°
Efficiency 91 %
Peak intensity 10.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2
FWHM 14.0°
Efficiency 88 %
Peak intensity 12.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salu, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

[CA11482_LXP2-D](#)