

"High Frequency Ceramic Solutions"

2.45/5.512 GHz Diplexer

P/N 2450DP15A5512

Detail Specification: 01/13/2003


Page 1 of 2

Part Number	Frequency (MHz)	Attenuation Low Band	Attenuation High Band	Return Loss
2450DP15A5512_	2400 - 2500	0.70 dB max.	15 dB min.	9.5 dB min.
	5150 - 5875	20 dB min.	0.9 dB max.	9.5 dB min.

Input Power	Impedance	Operating Temperature Range	Reel Qty
3 Watts max	50 Ω	-40 to +85°C	4000


Mechanical Dimensions

	L	W	T	a	b	c	g	p
Inches	0.079 ± .004	0.049 ± .004	0.034 ± .004	0.012 ± .004	0.008 ± .004	0.012 + .004/-0.008	0.014 ± .004	0.026 ± .002
mm	2.0 ± 0.1	1.25 ± 0.1	0.85 ± 0.1	0.30 ± 0.1	0.20 ± 0.1	0.30+0.1/-0.2	0.35 ± 0.1	0.65 ± 0.05




Terminal Configuration




No.	Function	No.	Function
1	GND	5	GND
2	Common Port (P1)	6	GND
3	GND	7	GND
4	High Freq. Port (P3)	8	Low Freq. Port (P2)



Mounting Considerations

Mount these devices with brown colored side facing up. Line width should be designed to provide 50Ω impedance matching characteristics.



-  Solder Resist
-  Land
-  Through-hole (ϕ 0.35)

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

“High Frequency Ceramic Solutions”


2.45/5.512 GHz Diplexer

Detail Specification: 01/13/2003


P/N 2450DP15A5512

Page 2 of 2

Insertion Loss



Return Loss



For the above graphs: Port 1 is Pin 2
(Common Port); Port 2 is Pin 8 (Low Band); Port 3 is Pin 4 (High Band)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Johanson:](#)

[2450DP15A5512E](#)