

Electronic housing - UM 72-PROFIL 100CM - 2907583

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Panel mounting base, length: 1000 mm, open, Lower part, Cross connection: without bus connector, color: green, width: 1000 mm, number of positions cross connector: not relevant, Note: required profile length = PCB length - 3.6 mm



The figure shows the variant UM 45-Profil CM

Your advantages

- ☑ Lateral elements with potential ground contact available from the PCB to the DIN rail (EMC)
- Fast assembly on standard NS 35 or NS 32 DIN rails

- High degree of mechanical stability by screwing the lateral elements to the profile
- The modules can be marked with Phoenix Contact marking material using the marking grooves in the press-drawn section



Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 365394
GTIN	4017918365394

Technical data

General

Housing type	Panel mounting base
Housing material	PVC
Color (RAL)	green (6021)

Ambient conditions

Ambient temperature (operation)	-15 °C 50 °C

Dimensions

Length	1 m
--------	-----



Electronic housing - UM 72-PROFIL 100CM - 2907583

Technical data

Dimensions

Width	1000 mm
Depth	89.6 mm

Standards and Regulations


Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2907583