



# IP68 SEALED USB PANEL MOUNT

## Mates with:

RCU (Single Port only)

### SPECIFICATIONS

For complete specifications see [www.samtec.com?RPBU](http://www.samtec.com?RPBU)

#### Insulator Material:

Black Liquid Crystal Polymer

#### Contact:

Phosphor Bronze

#### Current Rating:

4.2 A per pin

(1 pin powered)

#### Operating Temp Range:

-20 °C to +80 °C

Seal: Silicone

Lead-Free Solderable: Yes

### RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)

FILE NO. E111594

### DUST CAPS

- DCA-RPBU-01-01-A
- DCA-RPBU-02-01-A
- DCA-RPBU-01-01-B

| RPBU   | NO. OF PORTS  | PLATING  | TYPE  | LEAD STYLE  | OPTION   |              |   |   |   |     |                  |                  |                 |     |                  |                  |                  |
|--|---|--|---|---|--|--------------|---|---|---|-----|------------------|------------------|-----------------|-----|------------------|------------------|------------------|
|  | <div>-01<br/>= Single Port</div> <div>-02<br/>= Dual Port (-A only)</div> | <div>-S<br/>= 30 μ" (0.76 μm)<br/>Gold on contact,<br/>Matte tin on tail</div> | <div>-A<br/>= USB A Type</div> <div>-B<br/>= USB B Type</div> | <div>-VT<br/>= Vertical<br/>Through-hole</div> <div>-RA<br/>= Right-angle</div> | <div>-LC<br/>= Locking<br/>Clip (-VT only)</div> |              |   |   |   |     |                  |                  |                 |     |                  |                  |                  |
| <div><div><p>TYPE-B</p><p>-B-VT      -B-RA</p></div><div><p>TYPE-A</p><p>-A-VT      -A-RA</p></div></div> <table><tr><th>NO. OF PORTS</th><th>A</th><th>B</th><th>C</th></tr><tr><td>-01</td><td>(48.15)<br/>1.896</td><td>(39.10)<br/>1.539</td><td>(20.01)<br/>.788</td></tr><tr><td>-02</td><td>(69.80)<br/>2.748</td><td>(60.75)<br/>2.392</td><td>(42.00)<br/>1.654</td></tr></table> |   |  |   |   |  | NO. OF PORTS | A | B | C | -01 | (48.15)<br>1.896 | (39.10)<br>1.539 | (20.01)<br>.788 | -02 | (69.80)<br>2.748 | (60.75)<br>2.392 | (42.00)<br>1.654 |
| NO. OF PORTS   | A   | B  | C   |   |  |              |   |   |   |     |                  |                  |                 |     |                  |                  |                  |
| -01  | (48.15)<br>1.896  | (39.10)<br>1.539   | (20.01)<br>.788   |   |  |              |   |   |   |     |                  |                  |                 |     |                  |                  |                  |
| -02  | (69.80)<br>2.748  | (60.75)<br>2.392   | (42.00)<br>1.654  |   |  |              |   |   |   |     |                  |                  |                 |     |                  |                  |                  |

## Mates with:

RCU

### SPECIFICATIONS

For complete specifications see [www.samtec.com?RPCU](http://www.samtec.com?RPCU)

#### Insulator Material:

Black Liquid Crystal Polymer

#### Contact Material:

Phosphor Bronze

#### Operating Temp Range:

-20 °C to +80 °C

#### Shield Material:

Phosphor Bronze

#### Wire:

20 AWG (Power)

25 AWG (Signal)

28 AWG (Drain)

### DUST CAPS

- DCA-RPBU-01-01-A
- DCA-RPBU-01-01-B

| RPCU | PLATING   | CABLE LENGTH   | END 1 OPTION   | END 2 OPTION  |
|------|---|--|--|---|
|      | <b>-G</b><br>= 30 μ" (0.76 μm)<br>Gold on contact,<br>Nickel on shell | <b>-00.25</b><br>= (0.25 m) 9.84" Cable<br><br><b>-00.50</b><br>= (0.50 m) 19.68" Cable<br><br>Standard lengths<br><br>(Assembled Length<br>= Cable Length<br>+ (42.8 mm) 1.69") | <b>-AMS</b><br>= USB A Type,<br>Sealed<br><br><b>-BMS</b><br>= USB B Type,<br>Sealed | <b>-AM</b><br>= USB A Type,<br>Not Sealed<br><br><b>-BM</b><br>= USB B Type,<br>Not Sealed<br><br><b>-BC</b><br>= Blunt Cut |
|      |   |  |  |   |

**ALSO AVAILABLE**  
(MOQ Required)

- Other wire lengths

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications.

Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

[RPBU-01-S-A-VT](#) [RPBU-01-S-B-RA](#) [RPBU-01-S-A-VT-LC](#) [RPBU-01-S-A-RA](#) [RPBU-02-S-A-VT](#) [RPBU-02-S-A-VT-LC](#) [RPBU-01-S-B-VT](#) [RPBU-01-S-B-VT-LC](#) [RPBU-02-S-A-RA](#)