

1. HIDDEN LINES ARE USED TO SHOW POLARIZATION WHEN USING -N OPTION.

© REPRESENTS A CRITICAL DIMENSION 3. FFSD CABLE ASSEMBLIES ARE LEAD FREE

4. ALL ASSEMBLIES TO BE 100% ELECTRICALLY TESTED FOR SHORTS AND OPENS.

5. ALL ASSEMBLIES TO BE 100% HI-POT TESTED AT 630V.—(C) 6. STRAIN RELIEF TO WITHSTAND 5LB[22N] STRAIGHT PULL.

NOTE DELETED.

8. WHEN CUTTING CABLE TO LENGTH, CONDUCTORS SHOULD NOT EXTEND PAST THE CABLE INSULATION, EXTENDING LESS THAN 25% OF CABLE THICKNESS ON CONSECUTIVE AND LESS THAN 50% OF CABLE THICKNESS ON NON-CONSECUTIVE STRANDS IS CONSIDERED A PROCESS INDICATOR.

XX.XX[XX.X x 25.4]±1%

(SEE NOTE 8 & 11)

(No OF POS x .050[1.27]) + .165[4.19]

9. REFERENCE FFSD-XX-XX-X-N-XXX FOR CONNECTOR ASSEMBLY DIMENSIONS AND ITS REQUIREMENTS

10. COLORED WIRE MUST MATCH FIRST POSITION INDICATOR ON THE FIRST CONNECTOR FOR ALL OPTIONS WITH THE EXCEPTION OF -RW.

 $\langle \mathbb{C} \rangle$

FOR LENGTHS LESS THAN 12.5", TOLERANCE SHALL BE +/-.125, ALL OTHER LENGTHS SHALL BE +/-1%.

No OF POSITIONS -02 THRU -25 (PER ROW) **END ASSEMBLY** -S: SINGLE END -D: DOUBLE END

ASSEMBLY LENGTH (INCLUDES ADDED OPTION LENGTHS) ALL OPTIONS THAT USE -D"XX": 4.00 [101.6] MINIMUM ALL OTHER OPTIONS: 1.00 [25.4] MINIMUM LEAD STYLE

PLATING OPTIONS

- LEAVE BLANK FOR STANDARD, USE C-67-L

FFSD-XX-X-XX.XX-01-X-X-XXX

-S: USE C-67-S

-F: USE C-67-F


-RW: REVERSE WIRING (NOT AVAILABLE WITH -RN1 OR -RN2) ": DAISY CHAIN (MINIMUM 2.00[50.8], 1.00[25.4] INCREMENTS)
-R: REVERSED (-D"XX" OPTIONAL) (NOT AVAILABLE WITH -M OR -O) -RN1: REVERSE POLARIZATION NOTCH (NOT AVAILABLE WITH -RW OR -RN2) -RN2: REVERSE POLARIZATION NOTCH (NOT AVAILABLE WITH -RW OR -RN1) -M: MIDDLE REVERSE (REQUIRES -D"XX") (NOT AVAILABLE WITH -R OR -O)
-O: OUTSIDE REVERSE (REQUIRES -D''XX'') (NOT AVAILABLE WITH -R OR -M) -SR: STRAIN RELIEF (NOT AVAILABLE WITH -O, -M, -R, OR -D"XX") (SÓLD AS ASSÉMBLIES ONLY)

OPTION

STANDARD POLARIZATION NOTCH -N: POLARIZATION NOTCH

(NOT AVAILABLE IN -02 THRU -04) (LEAVE BLANK FOR -02, -03, -04)

> $XX.XX[XX.X \times 25.4]\pm1\%$ (SEE NOTE 8 & 11)



RED WIRE TO SIDE OF FIRST POS INDICATOR NOTCH DENOTES FIRST POSITION

FIG 1 (FFSD-10-D-XX.XX-01-X-N SHOWN)

.075 [1.91] **REF**

-N OPTION

.040 [1.02] **REF**

RED WIRE TO OPPOSITE SIDE OF FIRST POS. INDICATOR >

.120 [3.05] **REF**

.006[0.15] MAX

-RN1 OPTION

5

FIG 11 (FFSD-10-X-XX.XX-01-X-N-RW SHOWN)

TABLE 1	
PART	
FFSD-XX-01-X-N-XX	
CB-XX-30-7/38-025-GR	
FFSD-XX-01-X-N-SR1	
FFSR-XX-01	
FFSD-XX-01-X-N-SR2	
FFSR-XX-02	

-N OPTION

-RN2 OPTION

F:\DWG\MISC\MKTG\FFSD-XX-X-XX.XX-01-X-X-XXX-MKT.SLDDRW

UNLESS OTHERWISE SPECIFIED. DIMENSIONS ARE IN INCHES. TOLERANCES ARE:

DECIMALS **ANGLES** .XX: ±.01 [.3] .XXX: ±.005 [.13] 2° .XXXX: ±.0020 [.051]

PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN. MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART TO ANY LINAUTHORIZED DERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING SHEET SCALE: 2:1 INSULATORS: PBT UL94V-0, COLOR: BLACK CONTACT: BeCu WIRE: 30 AWG, 7/38, TINNED, STRANDED WITH GRAY PVC INSULATOR
PLATING: .000010 GOLD OVER .000050 NICKEL REMAINDER: .000200 REF TIN OVER .000050 NICKEL



FIG 2

(FFSD-10-S-XX.XX-01-X-N SHOWN)

(SAME AS FIG 1, DIFFERENT AS SHOWN)

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com


.050 x .050 DOUBLE ROW FEMALE IDC ASSEMBLY

FFSD-XX-X-XX.XX-01-X-X-XXX


BY: T NEWTON 02/15/2008 SHEET 1 OF 4



FIG 3 (FFSD-10-D-XX.XX-01-X-N-RN1 SHOWN) (SAME AS FIG 1, DIFFERENT AS SHOWN)





(FFSD-10-D-XX.XX-01-X-N-RN2 SHOWN) (SAME AS FIG 1, DIFFERENT AS SHOWN)




-RN1 = REVERSE NOTCH ON 1ST CONNECTOR ONLY
(NOT AVAILABLE WITH -R OPTION)
-RN2 = REVERSE NOTCH ON 2ND CONNECTOR ONLY
(NOT AVAILABLE WITH -R OPTION)

(REVERSE NOTCH NOT AVAILABLE WITH -RW OR ANY DAISY CHAIN OPTIONS)









 \preceq BOTH CONNECTORS REVERSED WHEN DAISY CHAINED $^{\succeq}$

FIG 6 (FFSD-10-D-XX.XX-01-X-N-DXX-R SHOWN) (SAME AS FIG 1, DIFFERENT AS SHOWN) (NOT AVAILABLE WITH -RN1 OR -RN2 OPTION) (2.00[50.8] MINIMUM, 1.00[25.4] INCREMENTS)

F:\DWG\MISC\MKTG\FFSD-XX-X-XX.XX-01-X-X-XXX-MKT.SLDDRW








FIG 7 (FFSD-10-D-XX.XX-01-X-N-DXX SHOWN) (SAME AS FIG 1, DIFFERENT AS SHOWN) (2.00[50.8] MINIMUM, 1.00[25.4] INCREMENTS)

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTED INC. THIS DOCUMENT SHALL NOT BE DISCLOSED. IN WHOLE REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 2:1



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

.050 x .050 DOUBLE ROW FEMALE IDC ASSEMBLY

FFSD-XX-X-XX.XX-01-X-X-XXX

BY: T NEWTON 02/15/2008 SHEET 2 OF 4

