

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Crimping pliers, for assembling the RJ45 plugs FL PLUG RJ45..., for assembly on site





Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	695.0 g
Custom tariff number	82060000
Country of origin	Germany

Technical data

Product type	Universal tools
Approval	EAC

Classifications

eCl@ss

eCl@ss 4.0	27230207
eCl@ss 4.1	27230207
eCl@ss 5.0	27230207
eCl@ss 5.1	27230207
eCl@ss 6.0	27230207
eCl@ss 7.0	27230207
eCl@ss 8.0	21049090

ETIM

ETIM 2.0	EC001423
ETIM 3.0	EC001423



Classifications

ETIM

ETIM 4.0	EC001423
ETIM 5.0	EC000385

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	39121008

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Data cable by the meter

Cable - FL CAT5 HEAVY - 2744814



CAT5-SF/UTP cable (J-02YS(ST)C HP 2 x 2 x 24 AWG), heavy-duty installation cable, 2 x 2 x 0.22 mm², solid conductor, shielded, outer sheath: 7.8 mm diameter, inner sheath: $5.75 \text{ mm} \pm 0.15 \text{ mm}$ diameter



Accessories

Network cable - FL CAT5 FLEX - 2744830



CAT5-SF/UTP cable (J-LI02YS(ST)C H 2 x 2 x 26 AWG), light-duty, flexible installation cable 2 x 2 x 0.14 mm 2 , stranded, shielded, outer sheath: 5.75 mm \pm 0.15 mm diameter

Data cable preassembled

Network cable - FL CAT5 HEAVY CONF/ - 2744827



CAT5-SF/UTP cable (J-02YS(ST)C HP 2 x 2 x 24 AWG), heavy-duty installation cable, 2 x 2 x 0.22 mm², solid conductor, shielded, outer sheath: 7.8 mm diameter, inner sheath: $5.75 \text{ mm} \pm 0.15 \text{ mm}$ diameter, preassembled on both sides with RJ45 plug, crossover or line

Network cable - FL CAT5 FLEX CONF/ - 2744843



CAT5-SF/UTP cable (J-LI02YS(ST)C H $2 \times 2 \times 26$ AWG), light-duty, flexible installation cable $2 \times 2 \times 0.14$ mm², stranded, shielded, outer sheath: 5.75 mm \pm 0.15 mm diameter, preassembled on both sides with RJ45 plug, crossover or line assignment

Die

Replacement die - CRIMPFOX LC-RJ 45S - 1207420




Die for the CRIMPFOX LC basic crimping pliers to crimp the VARIOSUB RJ45 male insert VS-08-ST-RJ45

Plug



Accessories

RJ45 connector - FL PLUG RJ45 GR/2 - 2744856





RJ45 connector - FL PLUG RJ45 GN/2 - 2744571

RJ45 connector, shielded, with bend protection sleeve, 2 pieces, green for crossed cables, for assembly on site. For connections that are crossed, it is recommended that the connector set with green bend protection sleeves is used.



Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2744869