


A 14mm wide potentiometer for audio, visual, electronic musical instruments and various applications



Typical Specifications



Items	Specifications
Total resistance tolerance	±20%
Maximum operating voltage	50V AC for AC only
Total rotational angle	300° ±5°
Rotational torque	3 to 20mN·m
Operating life	15,000 cycles
Operating temperature range	-10°C to +70°C

Product Line

Number of resistor elements	Mounting direction	Bushing	Shaft type	Length of the shaft LM ₁ (mm)	Center detent	Total resistance (k Ω)	Resistance taper	Application	Minimum order unit (pcs.)		Products No.	Drawing No.				
									Japan	Japan						
Dual-unit (Not applicable to DC)	Vertical type	Without	Flat	15	Without	10	1B	For tone	1,200	2,400	RK14K1230A2X	2				
				25					800	1,600	RK14K1230A0X					
				20		50	15A	For vol.	1,000	2,000	RK14K12C0A1S					
				25					800	1,600	RK14K12C0A0T					
		With		20	With	100	1B	For tone	1,000	2,000	RK14K1240062	4				
				25		10			800	1,600	RK14K1240036					
				27.5		100					RK14K1240D04					
				32.5	Without	10			15A	For vol.	800		1,600	RK14K1240A4S		
	27.5	50	RK14K12D0A1X													
	Horizontal type	Without	15	Without		10	1B	For tone						1,200	2,400	RK14K12A0A3C
			25			50						800		1,600	RK14K1210A1B	
		With	22.5		With	10			15A	1,000	2,000	RK14K1220A0F	3			
						20						1B		RK14K1220024		
				Without	50	15A	For vol.	RK14K1220A25								
					10			RK14K12B0A0E								
				50		RK14K12B0A0R										

Notes

- Other varieties are also available. Refer to "Other Specifications" (P.379).
- Nut and washer are not attached. Please specify if required.

Packing Specifications

Tray
















Length of the shaft LM ₁ (mm)	Number of packages (pcs.)		Export package measurements (mm)
	1 case / Japan	1 case / export packing	
15	1,200	2,400	374×532×240
20 to 22.5	1,000	2,000	
25 or more	800	1,600	

Refer to P.379 for other specifications.
Refer to P.380 for ordering products not listed.
Refer to P.383 for soldering conditions.

RK14K 14mm Size Insulated Shaft Snap-in Type

Dimensions

Unit:mm

No.	Photo	Style	PC board mounting hole dimensions (Viewed from mounting side)															
1	Horizontal type without bushing RK14K121 (For tone control) RK14K12A (For vol. control) 	<table><tr><td>LM₁</td><td>15</td><td>25</td></tr><tr><td>ℓ₁</td><td>4.5</td><td>12</td></tr></table>  <td></td>	LM ₁	15	25	ℓ ₁	4.5	12										
LM ₁	15	25																
ℓ ₁	4.5	12																
2	Vertical type without bushing RK14K123 (For tone control) RK14K12C (For vol. control) 	<table><tr><td>LM₁</td><td>15</td><td>20</td><td>25</td></tr><tr><td>ℓ₁</td><td>4.5</td><td>7</td><td>12</td></tr></table>  <td></td>	LM ₁	15	20	25	ℓ ₁	4.5	7	12								
LM ₁	15	20	25															
ℓ ₁	4.5	7	12															
3	Horizontal type with bushing RK14K122 (For tone control) RK14K12B (For vol. control) 	 <td></td>																
4	Vertical type with bushing RK14K124 (For tone control) RK14K12D (For vol. control) 	<table><tr><td>LM₁</td><td>20</td><td>25</td><td>27.5</td><td>32.5</td></tr><tr><td>L₁</td><td>12.5</td><td>17.5</td><td>20</td><td>25</td></tr><tr><td>ℓ₁</td><td>7</td><td>12</td><td>12</td><td>12</td></tr></table>  <td></td>	LM ₁	20	25	27.5	32.5	L ₁	12.5	17.5	20	25	ℓ ₁	7	12	12	12	
LM ₁	20	25	27.5	32.5														
L ₁	12.5	17.5	20	25														
ℓ ₁	7	12	12	12														

14mm Size Insulated Shaft Snap-in Type / Other Specifications

In addition to the products listed, we can accommodate the follow specifications.

Total Resistance Variety

Total resistance (k Ω)	5	10	20	50	100
--------------------------------	---	----	----	----	-----

Resistance Taper





Resistance taper	15A	1B	3B	15C
------------------	-----	----	----	-----

Tapped Types are Also Available


RK14K12 (for audio volume control) is also available with tap.

Shaft Variety


Unit:mm

Style		Without bushing				With bushing					
		Horizontal type		Vertical type		Horizontal type		Vertical type			
											
Detail dimensions	LM ₁	15	20	25	30	20	22.5	25	27.5	30	32.5
	L ₁	—	—	—	—	12.5	15	17.5	20	22.5	25
	ℓ_1	4.5	7	12	12	7	7	12	12	12	12
	L _B	—	—	—	—	5	5	5	5	5	5

Knob dimensions



LM₁ =15 only application



Terminal Layout / Circuit Diagram

Without tap for volume	With tap for volume	For tone and for volume (15C)

Note

Marked are specifications recommended by Alps.

Refer to P.380 for ordering products not listed.

14mm Size Insulated Shaft Snap-in Type / Ordering Products Not Listed

When ordering product varieties that are not listed, specify referring to the examples below.

Sample Part Number

R K 1 4 K 1 2 4 0 — **F 2 5** — **C 0** — **B 1 0 3**

Model type

Code	Model type
1	Horizontal type without bushing for tone
2	Horizontal type with bushing for tone
3	Vertical type without bushing for tone
4	Vertical type with bushing for tone
A	Horizontal type without bushing for vol.
B	Horizontal type with bushing for vol.
C	Vertical type without bushing for vol.
D	Vertical type with bushing for vol.

Shaft type

Code	Shaft type
F	Flat

*Only available in flat format.

Length of the shaft LM₁ (mm)

Code	Length of the shaft	Code	Length of the shaft
15	15	25	25
20	20	30	30
22	22.5	32	32.5
27	27.5	—	—


Detent

Code	Center detent
C0	Without
C1	With

Resistance taper

Code	Resistance taper	Code	Resistance taper
A	15A	C	15C
B	1B	V	3B

B : For tone & general (Model type : 1, 2, 3, 4)
V : For vol. (Model type : A, B, C, D)



Total resistance

Code	Total resistance (k Ω)	Code	Total resistance (k Ω)
502	5	503	50
103	10	104	100
203	20	—	—

Note

Marked are specifications recommended by Alps.

Insulated Shaft Potentiometers

List of Varieties

Type		9mm size			11mm size	12mm size		14mm size
Series		RK09K11 RK09D11	RK09K12	RK09Y11L	RK11K	RK12L12	RK12L115	RK14K
		Single-unit	Dual-unit	Single-unit	Single-unit	Dual-unit	Single-unit	Dual-unit
Photo								
Terminal mounting		Vertical / Horizontal		Horizontal	Vertical / Horizontal		Vertical	Vertical / Horizontal
Bushing		Without			With / Without	Without	With	With / Without
Operating temperature range		-10℃ to + 70℃					-40℃ to + 85℃	-10℃ to + 70℃
Operating life		5,000 cycles	10,000 cycles	1,000,000 cycles	15,000 cycles			
Available for automotive use		—	—	—	—	—		—
Life cycle								
Electrical performance	Total resistance (k Ω)	5, 10, 20, 50, 100, 200		10	5, 10, 20, 50, 100, 200		5, 10, 20, 50, 100	5, 10, 20, 50, 100, 200
	Resistance taper	15A, 1B, 3B, 15C		B	15A, 1B, 3B, 15C		15A, 1B, 3B	15A, 1B, 3B, 15C
	Total resistance tolerance	±20%	±30%	±30%	±20%			
	Rated power	0.05W	0.03W	0.01W	0.05W			
	Maximum operating voltage	50V AC 20V DC	50V AC for AC only	50V AC 5V DC	50V AC 20V DC	50V AC for AC only	50V AC 20V DC	50V AC for AC only
	Gang error	—	-40dB to 0dB 3dB max.	—	—	Volume control -40dB to 0dB 3dB max. For tone control within 2dB at center	—	Volume control -40dB to 0dB 3dB max. For tone control within 2dB at center
	Insulation resistance	100MΩ min. 250V DC			100MΩ min. 500V DC	100MΩ min. 250V DC		
	Voltage proof	250V AC for 1minute			500V AC for 1minute	300V AC for 1minute		
	Center-taps	Without			Without / With	Without		Without / With (Volume control)
Mechanical performance	Detent	Without, Center		Without	Without, Center	Without	Custom	Without, Center
	Stopper strength	0.3N·m		—	Without bushing 0.5N·m With bushing 0.6N·m	0.5N·m		0.6N·m
	Push-pull strength	50N max.		30N max.	80N max.			
	Vibration	10 to 55 to 10Hz/min., the amplitude is 1.5mm for all the frequencies, in the 3 direction of X, Y and Z and for 2 hours respectively						
Shaft configuration		Flat type, Knob type, Screwdriver type		Flat type				
Terminal style		Insertion						
Page		361 381(RK09D117)		368	369	373 381(RK12L12H, RK12L127)	376	377

Insulated Shaft Potentiometers Soldering Conditions	383
Potentiometers Cautions	439
Potentiometers Measurement and Test Methods	441
Potentiometers Resistance Taper	443

Note

● Indicates applicability to all products in the series.

■ Reference for Manual Soldering

Series	Tip temperature	Soldering time	No. of solders
RK09D, RK09K, RK09Y11L, RK11K, RK12L, RK12L115, RK14K	350°C max.	3s max.	1 time

■ Reference for Dip Soldering

Series	Preheating		Dip soldering		No. of solders
	Soldering surface temperature	Heating time	Soldering temperature	Soldering time	
RK12L	100°C	1 min. max.	260°C max.	5s max.	2 time max.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ALPS:

[RK14K12C0A0T](#) [RK14K12B0A0R](#) [RK14K1230A0X](#) [RK14K12C0A1S](#) [RK14K1230A2X](#) [RK14K1240D04](#)
[RK14K1240062](#) [RK14K1220A25](#) [RK14K1240036](#) [RK14K1240A4S](#) [RK14K12D0A18](#) [RK14K1220A0F](#)
[RK14K12D0A1X](#) [RK14K1210A1B](#) [RK14K12A0A3C](#) [RK14K1220024](#) [RK14K12B0A0E](#) [RK14K1240-F32-C0-B104](#)
[RK14K1220025](#) [RK14K1240A4S HARDWARE](#) [RK14K1220F25C0C104](#) [RK14K1220-F25-C0-A103](#) [RK14K1240-F20-](#)
[C0-B103](#) [RK14K1240-F32-C0-A503](#) [RK14K1240F0B103 HARDWARE](#) [RK14K1240D1M](#) [RK14K1240-F32-C0-B103](#)
[RK14K1240-F32-C1-B103](#) [RK14K12B0A0E HARDWARE](#) [RK14K1240-F32-C0-A104](#) [RK14K124003Y](#) [RK14K1220-](#)
[F25-C1-B103](#) [RK14K1240-F32-C1-B104](#)