

# Model 72937 IEC Insulated BNC (M) to two 4 mm banana jacks



#### **Features**


- IEC Insulated BNC (M) to two 4mm banana iacks.
- Adapter converts test instrument safety banana leads to BNC configuration for added shielding and safety.
- Rating: 500V Cat I, 150V Cat II




Connector body: Nickel plated BrassCenter Contact: Gold Plated Brass

Dielectric: White PTFEInsulation: Polyamide

Banana Jack: Nickel plated Brass





### **Specifications**

Max Current	ЗА
Max Voltage	500V CAT I, 150V CATII

#### **Ordering Information**

Model: 72937

**USA:** Sales: 800-490-2361 Fax: 888-403-3360 **Europe:** 31-(0) 40 2675 150 **International**: 425-446-5500

e-mail: <a href="mailto:technicalsupport@pomonatest.com">technicalsupport@pomonatest.com</a>
Where to Buy: <a href="mailto:www.pomonaelectronics.com">www.pomonaelectronics.com</a>

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona: 72937