



803006A09M020

no poles 3-5 pole cable type #22/3-5 PVC YELLOW cable length 020----2 Meters 100----10 Meters

CONNECTOR SPECIFICATION:

VOLTAGE RATING	250 VAC/VDC
AMPERAGE RATING	max. 4 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-20°C TO 105°C
UL CERTIFICATIONS	UL RECOGNIZED, FILE NO. E152210
ASSEMBLY	RoHS COMPLIANT

COMPONENT	MATERIAL	FINISH
LABEL	MYLAR	BLACK/YELLOW
COUPLER	BRASS	NICKEL PLATED
PIN CONTACT	COPPER ALLOY	GOLD OVER NICKEL
INSERT	NYLON	BLACK
OVERMOLD	PUR	YELLOW
CABLE- 22/AWG CONDUCT. 300V	JACKET: PVC	JACKET: YELLOW

MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH
1200650200	803006A09M020	6.56' +3.5" -0 [2.0M +89 -0]
1200650414	804006A09M020	6.56' +3.5" -0 [2.0M +89 -0]
1200650523	805006A09M020	6.56' +3.5" -0 [2.0M +89 -0]
1200650533	805006A09M100	32.81' +12.5" -0 [10.0M +318 -0]

UPDATED FOR PART NUMBER MATRIX EC NO: IPG2014-0988 DRWN: GGUSTAFS 11/26/13 CHKD: TWOLDEGE APPR: BWOODMAN 2010/01/25	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
		mm	INCH	IN/MM	NTS	INCH	
		4 PLACES ±---	±---	DRAWN BY DATE	MICRO-CHANGE ASSEMBLY 3-5 POLE MA STR 22/AWG YELLOW PVC CABLE MOLEX INCORPORATED DOCUMENT NO. SD-120065-028 SHEET NO. 1 OF 1		
	3 PLACES ±---	±.005	GGUSTAFS 2013/11/26				
2 PLACES ±.13	±.010	CHECKED BY DATE					
1 PLACE ±.25	±.020	RE 2010/01/21	APPROVED BY DATE				
ANGULAR ± .5 °		NSTAUDIG 2010/01/25	MATERIAL NO.				
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE CHART				
			SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[1200650414](#)