

Short-circuit connector - KSS 3- 6 - 0309523

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Short-circuit connector, Number of positions: 3, Color: black



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 001032
Weight per Piece (excluding packing)	5.81 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Technical data

Color	black
Material	Copper
Number of positions	3
Pitch	6.00 mm
Flammability rating according to UL 94	V2

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306

Short-circuit connector - KSS 3- 6 - 0309523

Classifications

eCl@ss

eCl@ss 5.0	27061801
eCl@ss 5.1	27141190
eCl@ss 6.0	27141190
eCl@ss 7.0	27141190
eCl@ss 8.0	27141140

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000448
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[0309523](#)