

# Product: <u>8759</u> ☑

# Audio Cable, #20-1pr, TC, O/A Braid, CM



# **Product Description**

20 AWG stranded (7x28) tinned copper conductors, PVC insulation, twisted pair, tinned copper spiral wrapped shield (90% coverage), PVC jacket.

#### **Technical Specifications**

#### **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

## **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
20	7x28	TC - Tinned Copper	0.038 in	1
Condu	uctor Count:		2	
Total Number of Pairs:		1		

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.07 in	0.016 in

### Color Chart

NumberColor1Black & Red

#### **Outer Shield Material**

Туре	Material	Coverage [%]
Spiral Serve / Screen	TC - Tinned Copper	90 %

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.199 in	0.025 in

#### **Electrical Characteristics**

Nominal Conductor DCR Nominal Conductor DCR Conductor Resistance   10 Ohm/1000ft 10 Ohm/1000ft	Conductor DCR				
10 Ohm/1000ft 10 Ohm/1000ft		Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance		
		10 Ohm/1000ft	10 Ohm/1000ft		

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
47 pF/ft	79 pF/ft

#### Inductance

Nominal Inductan	Ce
0.17 µH/ft	

Impedance

#### Current

Max. Recommended Current [A] 3.9 Amps per conductor @ 25°C

#### Voltage

UL Voltage Rating 300 V RMS

# **Temperature Range**

UL Temp Rating:	80°C
Operating Temp Range:	-20°C To +80°C

## **Mechanical Characteristics**

Bulk Cable Weight:	23 lbs/1000ft
Max Recommended Pulling Tension:	25 lbs
Min Bend Radius/Minor Axis:	2 in

#### **Standards**

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2095 (300 V 80°C)
CPR Euroclass:	Eca

# **Applicable Environmental and Other Programs**

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

# Suitability

Suitability - Indoor:	Yes

# Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

# Part Number

#### Variants

ltem #	Color	Putup Type	Length	UPC
8759 060U500	Chrome	UnReel	500 ft	612825215448
8759 0601000	Chrome	Reel	1,000 ft	612825215080
8759 060U1000	Chrome	UnReel	1,000 ft	612825215097
Footnote:				RATE REEL PUT

# History

Update and Revision:

Revision Number: 0.242 Revision Date: 04-28-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 8759 060U500