




REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	D1	REVISED PER ECO-11-005294	29APR2011	RK	HMR
	E	REVISED PER ECO-13-019231	09DEC2013	DR	RB



776532-2
(GRAY TPA)
SCALE 2:1




776532-3
(YELLOW TPA)
SCALE 2:1




776532-4
(GREEN TPA)
SCALE 2:1


- 1 MATERIAL: 15% GLASS FILLED THERMOPLASTIC
COLOR: BLACK
- 2 MATERIAL: 15% GLASS FILLED THERMOPLASTIC
COLOR: (SEE TABLE)
- 3 MATERIAL: SILICONE
COLOR: RUST
- 4 MATERIAL: 15% GLASS FILLED THERMOPLASTIC
COLOR: RED
5. RECOMMENDED WIRE DIAMETER RANGE IS 1.30 TO 2.54mm.
- 6 MATERIAL: SILICONE
COLOR: TAN



776532-1 SHOWN



SECTION A-A



SCALE 2:1

GREEN	776532-4
YELLOW	776532-3
GRAY	776532-2
RED	776532-1
TPA COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±
FINISH	-

DWN
B. SIMPSON
05NOV2002

CHK
D. KLEIN
05NOV2002

APVD
D. KLEIN
05NOV2002

PRODUCT SPEC
108-2184

APPLICATION SPEC
114-13065

WEIGHT
16±1g

Customer Drawing

TE Connectivity

NAME
PLUG ASSEMBLY,
8 POSITION, DUAL ROW,
REDUCED DIA WIRE SEAL, AMPSEAL 16

SIZE
A2

CAGE CODE
-

DRAWING NO
C-776532

RESTRICTED TO
-

SCALE
4:1

SHEET
1

OF
1

REV
E

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[776532-4](#)