


5mm
LED CBI® Circuit Board Indicator
3 Leaded, Bi-Color, Common Cathode

Dialight

550-3x09



PART NO.

550-3509

COLOR

Red/Green

550-3609

Yellow/Green

To order any of the 550-3x09 part numbers with Reverse Polarity (Red or Yellow Anode Right; Green Anode Left), please add -010 to the part numbers shown above.

NEW

Features

- Common Cathode simplifies design, and the red/green LED provides yellow-orange as a third color
- Multiple CBIs form horizontal LED arrays on 7.62mm (0.300") center-lines.
- High Contrast, UL 94 V-0 rated, black housing
- Oxygen index: 32%
- Polymer content: PBT, 0.414 g
- Housing stand-offs facilitate PCB cleaning
- Solderability per MIL-STD-202F, method 208F
- LEDs are safe for direct viewing per IEC 825-1, EN-60825-1

Tolerance note: As noted, otherwise:

- LED Protrusion: ± 0.04 mm [± 0.016]
- CBI Housing: ± 0.02 mm [± 0.008]

PART NUMBER ORDERING CODE	
5 5 0 - 3 x 0 9 - 0 1 0	
Reverse Polarity Option 1) Red or Yellow Anode Right; Green Anode Left	

-010 Ordering Code Suffix required ONLY for Reverse Polarity Option

Typical Operating Characteristics (T_A=25°C)

See LED data sheet for additional information


See page 6-55 and 6-56 for Reference Only LED Drive Circuit Examples. See page 6-57 for Pin Out

Part Number	Color	Peak Wavelength nm	I _V mcd	V _F Volts	Test Current (mA)	Viewing Angle 2θ%	LED Data sheet	Page #
550-3509	Red/Green	635/565	5/8	2.1/2.3	10	65°	521-9450	6-45
550-3609	Yellow/Green	583/565	5/8	2.1/2.1	10	65°	521-9460	6-45

**5mm Discrete LED
Bi-Color
3 Leaded, Non-Tinted, Diffused**

Dialight

521-9450, -9460



<u>PART NO.</u>	<u>LED COLOR</u>
521-9450	Red/Green
521-9460	Yellow/Green NEW

MOUNTING CLIP: 515-0004
located on page 6-48

ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$)

	Red/Green -9450	Yellow/Green -9460
Power Dissipation (mW)	135/135	135/135
Forward Current (mA)	25/25	25/25
Derating (mA/ $^\circ\text{C}$) From 50 $^\circ\text{C}$ 1. From 40 $^\circ\text{C}$.5/.5	.5/.5
Peak Current (mA)	90/90	90/90
<i>Pulse width = 10 μs</i>		
Operating Temperature ($^\circ\text{C}$)	-20/+85	-20/+85
Storage Temperature ($^\circ\text{C}$)	-55/+100	-55/+100
Soldering Temperature	260 $^\circ\text{C}$, 5 seconds, 1.6 mm from case	

Solder Adherence per MIL-STD-202E, Method 208C

OPERATING CHARACTERISTICS ($T_A=25^\circ\text{C}$)

	Red/Green -9450	Yellow/Green -9460
Luminous Intensity (mcd) $I_F=10\text{mA}$	Min. Typical	2.1/4.2 5/8
Peak Wavelength (nm) λ Peak	Typical	635/565
Viewing Angle ($2\Theta^\circ$)	Typical	65 $^\circ$
Forward Voltage (V) $I_F=10\text{mA}$	Typical Max.	2.1/2.3 2.5/2.7

Θ° is the off axis angle at which the luminous intensity is half the axial luminous intensity

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

[550-3509-801F](#) [550-3509-802F](#) [550-3509-803F](#)