



**Part Number: 82761**

Electronic, 2 C #22 Str TC, FEP Ins, OS, PVC Jkt, CMP

[Request Sample](#)

**Product Description**

Electronic Cable, 2 Conductor 22AWG (7x30) Tinned Copper, FEP Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMP

**Technical Specifications**

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	22 AWG

**Insulation**

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.0065 in

**Color Chart**

Number	Color
1	Black & Red

**Outer Shield Material**

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil® with shorting fold	100 %	TC - Tinned Copper	22	Stranded mm

**Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.118 in	0.015 in

**Construction and Dimensions**

**Stranding**

Lay Direction	Twists
Left Hand	8 twist/ft

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR
15 Ohm/1000ft	12 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
35 pF/ft	67 pF/ft

**Inductance**

**Nominal Inductance**

0.16 µH/ft

**Impedance****Nominal Characteristic Impedance**

42 Ohm

**Current**

Element	Max. Recommended Current [A]
10C Temperature Rise	2.8 Amps per conductor @ 25°C ambient

**Voltage****UL Voltage Rating**

300 V RMS

**Temperature Range**

Operating Temp Range:	-20°C To +75°C
-----------------------	----------------

**Mechanical Characteristics**

Bulk Cable Weight:	11 lbs/1000ft
Max Recommended Pulling Tension:	27 lbs
Min Bend Radius/Minor Axis:	1.25 in

**Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
CPR Euroclass:	Eca

**Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

**Suitability**

Suitability - Indoor:	Yes
-----------------------	-----

**Flammability, LSOH, Toxicity Testing**

UL Flammability:	NFPA 262
CSA Flammability:	FT6
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

**Plenum/Non-Plenum**

Plenum (Y/N):	Yes
---------------	-----

**Part Number**

Non-Plenum Number:	8761
--------------------	------

**Variants**

Item #	Color	UPC	Length	Footnote
82761 8771000	Natural	612825197782	1,000 ft	C
82761 8775000	Natural	612825197799	5,000 ft	
82761 877U1000	Natural	612825197768	1,000 ft	

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.