THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	REVISED PER ECO-16-005106	05APR2016	NK	MZ
	H	REVISED PER ECO-17-013721	15NOV2017	RS	MZ

T	L	LH	(FREE DIA)	MAT'L (NOTE)	MATING PIN ø REF	PLATING NOTE NO.	NUM LOUV	MAT'L THK	REF	PART NO.	
15°	[.690]	[.050]	[0.69]	6	12.7[.500]	9-2	16	0.15[.006]	--	5-192033-3	
15°	[.690]	[.052]	[1.18]	6	--	PREPL	32	0.20[.008]	--	5-192033-2	OBSOLETE
15°	[.690]	[.052]	[4.00]	7	--	5-2	150	0.20[.008]	--	5-192033-1	OBSOLETE 11
45°	[.700]	[.052]	[.95]	7	--	5-2	25	0.20[.008]	--	~~5-192033-0~~	OBSOLETE
15°	[.69]	[.052]	[.90]	7	--	5-2	22	0.20[.008]	--	4-192033-9	11
15°	[.69]	[.052]	[.55]	7	--	5-2	13	0.20[.008]	--	4-192033-8	OBSOLETE
15°	[.69]	[.050]	[3.00]	7	26.21[1.032]	UNPL	41	0.10[.004]	--	4-192033-7	
15°	[.69]	[.050]	[.99]	7	20.32[.800]	UNPL	26	0.15[.006]	--	4-192033-6	
15°	[.69]	[.050]	[1.35]	7	28.57[1.125]	5	35	0.10[.004]	--	~~4-192033-5~~	OBSOLETE
45°	[.70]	[.050]	[4.00]	7	44.45[1.750]	5	55	0.15[.006]	--	~~4-192033-4~~	OBSOLETE
45°	[.70]	[.050]	[.95]	7	20.06[.790]	--	25	0.15[.006]	01321	~~4-192033-3~~	OBSOLETE
45°	[.70]	[.050]	[3.00]	7	34.92[1.375]	5	44	0.15[.006]	01230	~~4-192033-2~~	OBSOLETE
15°	[.69]	[.050]	[3.00]	7	34.92[1.375]	5	44	0.15[.006]	01229	4-192033-1	
15°	[.69]	[.050]	[3.00]	7	34.92[1.375]	5	44	0.10[.004]	01199	4-192033-0	
15°	[.69]	[.050]	[3.00]	7	33.40[1.315]	5	42	0.15[.006]	01233	3-192033-9	11
									01306	3-192033-8	
15°	[.69]	[.050]	[3.00]	7	32.25[1.270]	4-2	41	0.15[.006]	01262	3-192033-7	OBSOLETE
15°	[.69]	[.050]	[3.00]	7	32.25[1.270]	5	41	0.15[.006]	01260	3-192033-6	
15°	[.69]	[.050]	[1.02]	7	22.22[.875]	UNPL	27	0.15[.006]	--	3-192033-5	
15°	[.69]	[.050]	[1.50]	7	31.75[1.250]	5	39	0.15[.006]	01232	~~3-192033-4~~	OBSOLETE
15°	[.69]	[.050]	[3.00]	7	30.15[1.187]	5	L	0.15[.006]	01192	3-192033-3	11
15°	[.69]	[.050]	[2.50]	7	26.21[1.032]	4-2	32	0.10[.004]	01261	3-192033-2	OBSOLETE
OBSOLETE									--	3-192033-1	OBSOLETE
15°	[.69]	[.050]	[2.50]	7	26.21[1.032]	5	32	0.10[.004]	01185	3-192033-0	
15°	[.69]	[.050]	[2.50]	7	26.21[1.032]	UNPL	32	0.10[.004]	01265	2-192033-9	11
45°	[.70]	[.050]	[1.18]	7	25.40[1.000]	5	32	0.15[.006]	01179	2-192033-8	OBSOLETE
15°	[.69]	[.050]	[1.15]	8	25.40[1.000]	UNPL	31	0.15[.006]	01269	2-192033-7	
15°	[.69]	[.050]	[1.15]	7	25.40[1.000]	5	31	0.15[.006]	01175	2-192033-6	
OBSOLETE									01174	2-192033-5	OBSOLETE
15°	[.69]	[.050]	[1.15]	7	24.13[.950]	UNPL	31	0.15[.006]	01173	2-192033-4	11
15°	[.69]	[.050]	[1.11]	7	23.36[.920]	5	30	0.15[.006]	--	2-192033-3	OBSOLETE
15°	[.69]	--	--	--	--	--	--	--	01254	2-192033-2	OBSOLETE
15°	[.69]	[.052]	[1.05]	7	22.22[.875]	5	28	0.20[.008]	01168	2-192033-1	OBSOLETE 11
15°	[.69]	[.050]	[1.05]	7	22.22[.875]	5	28	0.15[.006]	01167	2-192033-0	
15°	[.69]	[.050]	[1.02]	7	22.22[.875]	3-2	27	0.15[.006]	01310	1-192033-9	
									01250	1-192033-8	SUPERSEDED 11
OBSOLETE									01251	1-192033-7	OBSOLETE
OBSOLETE									01253	1-192033-6	OBSOLETE
15°	[.69]	[.050]	[2.00]	7	22.22[.875]	5	27	0.10[.004]	01257	1-192033-5	11
15°	[.69]	[.050]	[1.02]	7	22.22[.875]	UNPL	27	0.10[.004]	01256	1-192033-4	OBSOLETE
									01267	1-192033-3	OBSOLETE
									01204	1-192033-2	11
									01166	1-192033-1	OBSOLETE
15°	[.69]	[.050]	[1.02]	7	21.38[.842]	5	27	0.15[.006]	01164	~~1-192033-0~~	OBSOLETE
15°	[.69]	[.050]	[.99]	7	21.38[.842]	5	26	0.15[.006]	01287	192033-9	11
15°	[.69]	[.050]	[.95]	7	20.62[.812]	5	25	0.15[.006]	01252	192033-8	OBSOLETE
OBSOLETE			[.99]	7	20.32[.800]	1-2	26	0.15[.006]	01239	192033-7	OBSOLETE
15°	[.69]	[.052]	[.95]	7	20.0[.787]	5	25	0.20[.008]	01161	192033-6	OBSOLETE 11
15°	[.69]	[.050]	[.95]	7	20.0[.787]	5	25	0.15[.006]	01314	~~192033-5~~	OBSOLETE
									01156	192033-4	OBSOLETE 11
15°	[.69]	[.052]	[.92]	7	19.05[.750]	5	24	0.20[.008]	01155	192033-3	OBSOLETE
15°	[.69]	[.052]	[.92]	7	19.05[.750]	UNPL	24	0.20[.008]	01224	192033-2	11
15°	[.69]	[.052]	[.90]	7	19.05[.750]	5	23	0.20[.008]	01249	192033-1	OBSOLETE

VIEW A-A





1. FINISH: GOLD PLATE 10uIN MIN THICK.
2. FINISH: NICKEL PLATE 40uIN MIN THICK.
3. FINISH: GOLD PLATE 30uIN MIN THICK.
4. FINISH: SILVER PLATE 500uIN MIN THICK.
5. FINISH: SILVER PLATE 200uIN MIN THICK.
6. PLATING NOTES ARE TO BE INTERPRETED AS FOLLOWS, 4-2 AS 4 OVER 2.
7. MATERIAL: CDA172, BeCu.
8. MATERIAL: STAINLESS STEEL.
9. FINISH: GOLD PLATE 50uIN MIN THICK.

10 PRELIMINARY PART NUMBER.

11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± 0.25[.01]
3 PLC ± 0.125[.005]
4 PLC ± -
ANGLES ± -

MATERIAL: SEE TABLE
FINISH: SEE TABLE

DWN RA JAYNE 07-24-92
CHK -
APVD -
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -
CUSTOMER DRAWING

TE Connectivity

NAME: CONTACT BAND,FEMALE

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-192033	-

SCALE NTS SHEET 1 OF 1 REV H

192033

1471-9 (1/15)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

2-192033-0