



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A1	REVISED PER ECO-11-005030	30MAR11	HMR

COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
COMPONENT	MATERIAL	FINISH

CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.088
CONTACT	.023

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES  
 TOLERANCE ON  
 FRAC. DEC. ANGLES  
 ± 1/64 ±.005 ± °

DRAWN BY **KRW** DATE **9/10/79**  
 CHECKED BY **R.R.SMITH** 9/11/79  
 APP'D BY **GH** 9/12/79  
 USE ASS'Y PROCEDURE  
 NO. AP. **10-002**  
**408-04795**  
 CUSTOMER DRAWING

**STE** TE Connectivity

TITLE **OSSM STRAIGHT CABLE PLUG DIRECT SOLDER ATTACHMENT**

SIZE <b>B</b>	CODE IDENT NO. <b>26805</b>	<b>1045351</b>	REV <b>A1</b>
---------------	-----------------------------	----------------	---------------

SCALE **8:1** SHEET **1 OF 1**

NOTES:  
 1. DESIGNED FOR USE WITH .085 DIA SEMI-RIGID CABLE

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1001-5004-02](#)