

# 40 Series

## Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

### FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

### SERIES SPECIFICATIONS

Series	Wattage	Ohms	Voltage
41	1.0	0.10-6K	150
42	2.0	0.10-8K	100
43	3.0	0.10-20K	200
45	5.0	0.10-70K	460
47	7.0	0.10-80K	670
40	10.0	0.10-150K	1000

Non-Inductive versions available. Insert "N" before tolerance code.  
Example: 42NJ27R

### CHARACTERISTICS

<b>Coating</b>	Conformal silicone-ceramic.
<b>Core</b>	Ceramic.
<b>Terminals</b>	Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
<b>Derating</b>	Linearly from 100% @ +25°C to 0% @ +275°C.
<b>Tolerance</b>	±5% (J type), ±1% (F type) (other tolerances available).
<b>Power rating</b>	Based on 25°C free air rating
<b>Overload</b>	Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.
<b>Temperature coefficient</b>	Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C
<b>Operating temp. range</b>	-55°C to 275°C

### DIMENSIONS

(in./mm max.)



Series	Wattage	Length	Diam.	Lead ga.
41	1.0	0.437 / 11.1	0.125 / 3.2	24
42	2.0	0.406 / 10.3	0.219 / 5.6	20
43	3.0	0.593 / 15.1	0.219 / 5.6	20
45	5.0	0.937 / 23.8	0.343 / 8.7	18
47	7.0	1.280 / 32.5	0.343 / 8.7	18
40	10.0	1.900 / 48.3	0.406 / 10.3	18

(continued)



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Ohmite:

[43J7R5](#) [41F560](#) [41F7R5](#) [45F75R](#) [45F47R](#) [45F62R](#) [45F27R](#) [45F40R](#) [45F22R](#) [45F20R](#) [45F25R](#) [45F68R](#)  
[41F500](#) [41F5R0](#) [45F82R](#) [45F35R](#) [45F30R](#) [45F39R](#) [45F33R](#) [40J22R](#) [42J120](#) [41F1R5](#) [45F680](#) [41F1R0](#) [41F150](#)  
[41F100](#) [45F600](#) [41F180](#) [42J1R5](#) [42J125](#) [43F600](#) [43J2K0](#) [43J6K0](#) [43F680](#) [43F35R](#) [43F47R](#) [43F82R](#) [43F33R](#)  
[43F39R](#) [43F25R](#) [43F10R](#) [43F15R](#) [43F12R](#) [43F50R](#) [43F56R](#) [43F75R](#) [43F27R](#) [43F18R](#) [43F20R](#) [43F40R](#)  
[43F22R](#) [43F30R](#) [41J2K0](#) [45J225](#) [40F200](#) [42J82R](#) [43F300](#) [40F220](#) [40F225](#) [45J2R2](#) [45J220](#) [45J680](#) [43F7R5](#)  
[41J150](#) [45J600](#) [45J1K0](#) [42J400](#) [42J470](#) [41F12R4](#) [42J450](#) [41F900](#) [45J270](#) [42J47R](#) [42J50R](#) [42J20R](#) [43F3R0](#)  
[42J18R](#) [42J68R](#) [43F390](#) [42J27R](#) [42J10R](#) [42J25R](#) [42J15R](#) [42J62R](#) [42J22R](#) [45J200](#) [42J12R](#) [43F350](#) [42J56R](#)  
[42J40R](#) [40F40K](#) [40F2K0](#) [40F7K0](#) [40F8K0](#) [40F3K0](#) [40F4K0](#) [40F6K0](#) [40F5K0](#) [40F9K0](#) [45J900](#)