






Contact arrangement / view from termination side



Assembling instruction



 DISTANCE FOR SAFETY
CONTACT MARKING MAX. 24 mm

- 1 SUITABLE CRIMP CONTACTS: SERIES HE/HA
OUTER DIMENSIONS OF INSULATION: MAX. ϕ 3,2 MM
- 2 SUITABLE HOOD SIZE 5; 7; 9; 11: SERIES HA; HD
SUITABLE INSERTION AND EXTRACTION TOOL:
SCREWDRIVER 0,5x3 DIN 5264
- 3 Strip lenght: Screw conection 10mm
Spring clamp conection 10mm Crimp conection 7.5mm
- 4 STANDARDS:
DIN EN 61984; DIN EN 60664-1

-  PACKAGING:
5 SETS IN A CARTON, PRE-MOUNTED
-  SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 300 PIECES
-  SPECIAL PACKAGING: Krauss-Maffei
PACKAGING UNIT: 150 PIECES
-  SPECIAL PACKAGING: AIS
PACKAGING UNIT: 250 PIECES
-  SPECIAL PACKAGING: WIELAND
PACKAGING UNIT: 100 PIECES

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[7-1103417-8](#)