




ISO9001:2008 Certified

Mechanical Specifications (mm)

D:	23.0	± max
T:	9.0	± max
Lead Diameter	1.0	± nom
S:	7.8	± nom
L:	38.0	± nom
Coating Lead Run Down (straight Leads)	4.0	± max
B:	9.20	± nom
C:	6.70	± nom



Electrical Specifications

Resistance:	30.0 Ω	± 20 %
Max Steady State Current upto 65°C:	5.00	A
Max Rec. Energy Rating:	150	J
Actual Failure Instantaneous Energy:	285	J
Maximum Capacitance @ 120 VAC:	10,300	μ f
Maximum Capacitance @ 240 VAC:	2,604	μ f
Maximum Capacitance @ 440 VAC:	602	μ f
Maximum Capacitance @ 680 VAC:	300	μ f
Resistance @ 100% Max Current:	0.23	Ω
Resistance @ 50% Max Current:	0.65	Ω
Body Temperature at 100% Max Current:	174.00	°C
Dissipation Constant:	45.4	mw/°C
Thermal Time Constant:	112	Sec.
Material Type (for Beta and Curve):	H	

MS22 30005

Date: 02/05/2009	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: a

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ametherm:](#)

[MS22 30005](#)