



- 1

COPPER ALLOY PER ASTM B301
- 2

1.27 μm [50 μin] MIN GOLD PER ASTM B488
OVER 2.54 μm [100 μin] MIN NICKEL PER
QQ-N-290 ON ENTIRE STOCK.
3.

APPLICATION TOOLING:
CRIMPING TOOL: M22520/23-01
DIE SET: M22520/23-02
LOCATOR: TYCO P/N 1738331-1
EXTRACTION TOOL: M81969/28-01
4.

WIRE ACCOMMODATED: 8 AWG
STRIP LENGTH: 9.60 [.378] - 10.10 [.398]
5.

THIS PRODUCT IS SOLD BY TYCO ELECTRONICS
UNDER A LICENSE FROM RADIAL SA

PRELIMINARY
NOT RELEASED FOR
PRODUCTION

Tyco PN - 1738019-1

DIMENSIONS : mm [inch]

THIS DRAWING IS A CONTROLLED DOCUMENT.		CHK	28MAR2004	Tyco Electronics Corporation Harrisburg, Pa 17105-3628	
DIMENSIONS: mm [INCHES]		CHK	APD	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		POWER CONTACT, PIN, CRIMP TERMINATION	
D P/LC ± =		APPLICATION SPEC		SIZE 5	
F P/LC ± =		SIZE		GPR	
B P/LC ± =		SIZE		GPR	
A P/LC ± =		SIZE		GPR	
ANGLES		SIZE		GPR	
FINISH		SIZE		GPR	
MATERIAL		SIZE		GPR	
CUSTOMER DRAWING		SIZE		GPR	
SCALE		SHEET		REV	
1:1		1 OF 1		Q	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1738019-1](#)