

# Printed-circuit board connector - EMSTBA 2,5/ 5-G-5,08 GY - 1703449

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, nominal current: 12 A, number of positions: 5, pitch: 5.08 mm, color: gray, contact surface: Tin




The figure shows a 10-position version of the product

## Your advantages

- Long-term stable press-in connection ensures high holding force without thermal load
- Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- Closed contour for optimum stability of the plug-in connection



## Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 50 pc   |
| GTIN         | <br>4 046356 652742 |
| GTIN         | 4046356652742   |

## Technical data

### Dimensions

|                          |          |
|--------------------------|----------|
| Pitch                    | 5.08 mm  |
| Dimension a              | 20.32 mm |
| Height                   | 9 mm     |
| Length of the solder pin | 4.2 mm   |
| Pin dimensions           | 1.7 mm   |

### General

|                                  |                 |
|----------------------------------|-----------------|
| Range of articles                | EMSTBA 2,5/..-G |
| Rated voltage (III/3)            | 250 V           |
| Connection in acc. with standard | EN-VDE          |
| Nominal current I <sub>N</sub>   | 12 A            |
| Color                            | gray            |

# Printed-circuit board connector - EMSTBA 2,5/ 5-G-5,08 GY - 1703449

## Technical data

### General

|                     |   |
|---------------------|---|
| Number of positions | 5 |
|---------------------|---|

### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|----------------------------------|--------|

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Approvals


### Approvals


#### Approvals


IECEE CB Scheme / VDE Gutachten mit Fertigungsüberwachung / EAC / cULus Recognized

#### Ex Approvals

### Approval details


|                    |   |   |                |
|--------------------|---|---|----------------|
| IECEE CB Scheme    |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-58978-B1B2 |
| Nominal voltage UN | 250 V   |   |                |
| Nominal current IN | 12 A  |   |                |

|   |   |   |          |
|---|---|---|----------|
| VDE Gutachten mit Fertigungsüberwachung |  | <a href="http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx">http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx</a> | 40004701 |
| Nominal voltage UN                      | 250 V   |   |          |
| Nominal current IN                      | 12 A  |   |          |

|     |   |         |
|-----|---|---------|
| EAC |  | B.01742 |
|-----|---|---------|

## Printed-circuit board connector - EMSTBA 2,5/ 5-G-5,08 GY - 1703449

### Approvals

|                    |   |   |                 |
|--------------------|---|---|-----------------|
| cULus Recognized   |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19931011 |
|                    | D   | B   |                 |
| Nominal voltage UN | 300 V   | 300 V   |                 |
| Nominal current IN | 10 A  | 15 A  |                 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1703449](#)