


Cover - BC 71,6 DKL S TRANS - 2896128

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Installation component housing, Housing cover, Cross connection: Component housing, Color: transparent, Width: 71.6 mm

Product Features

- Item is from the BC product range
- Conforms to DIN EN 43880
- Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	18.0 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

General

Housing type	Installation component housing
Housing material	Polyamide
Color	transparent

Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)



Cover - BC 71,6 DKL S TRANS - 2896128

Technical data

Dimensions

Width	71.6 mm
Technical data	
Flammability rating according to UL 94	V0
Standards and Regulations	
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC000886
ETIM 5.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized / EAC



Cover - BC 71,6 DKL S TRANS - 2896128

Approvals	,, -,,-,-,-,-,-,-,-,-,-,-,-,-,-,-,-,-,-
Ex Approvals	
Approvals submitted	
Approval details	
UL Recognized \$1	
EAC	
Accessories	
Accessories	
Fiber optics	
Component housing - HS	S LC-V-D3/ R2XC1-5,08 - 2202311
	Fiber optics Can be used for the BC housing range (housing must be processed), Color: transparent
Component housing - HS LC-V-D3/ R3XC1-5,08 - 2202312	
	Fiber optics Can be used for the BC housing range (housing must be processed), Color: transparent

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2896128