
Eagle Picher


The LTC-3PN series is a perfect match for applications which have little space but need a reliable, high energy source. This cell is available in three (3) printed circuit board (PCB) mounting configurations, with the flexibility to be designed for any mounting geometry. With 350 mAh packed into 0.0975 in², these small power sources will provide the solution for your electronic packaging requirements.



LTC-3PN PRODUCT FEATURES

- Compliant with lead-free RoHS and WEEE EC directives.
- · Low profile, prismatic design.
- Stainless steel construction provides corrosion resistance, hermetic seal and structural integrity.
- · Years of low rate continuous use.
- Stand-by use with 80% capacity retention after 15 years at room temperature.
- · Highly efficient utilization of valuable board space.
- Wave solderable (limit solder bath exposure to a maximum of 5 seconds).
- · High energy density compared to other chemistries.
- · No charging circuits required.
- Higher cell voltage allows for fewer cells and high reliability.
- Flat discharge characteristics provide optimum voltage regulation.
- Non-pressurized system allow for high temperature usage.
- · Ship unrestricted. IATA No. UN3090.
- · Underwriters Laboratories recognized component.

TYPICAL LTC-3PN DISCHARGE CHARACTERISTICS AT VARIED TEMPERATURES



DO YOU HAVE QUESTIONS

CONCERNING:

- · What size battery you need?
- · What is passivation and its effects?
- · What is the maximum rate of this cell?
- · Any other technical question?

If so, call our Engineers at 1-800-201-0215 or 1-417-625-1116 for detailed technical information.

Eagle Picher

Part Number	Voltage	Capacity (mAh)	Length (in.)	Width (in.)	Thickness (in.)	Weight (g)
LTC-3PN	3.5	350	0.60	0.65	0.265	4.6
LTC-3PN-S2	3.5	350	0.65	0.265	0.60	4.6
LTC-3PN-S4	3.5	350	0.60	0.265	0.65	4.6

SPECIFICATIONS LTC-3PN

Nominal Ope	en Circu	it Voltage, 25°C	3.67 volts
Nominal Wor	king Vol	tage, 25°C	3.5 volts
Nominal Cap	acity (3	50 hr. rate), 25°C	350 mAH
Volume			0.103 cu. in.
Weight			4.6 GMS
Operating Te	mperatu	re	40°C to +95°C

Case Material: 304 Stainless Steel, Hermetically Sealed (case negative polarity) Terminal and Support Pins are .030" dia. (solder tinned)

6 GMS +95°C negative polarity)


.60

POWER LEADS

SPECIFICATIONS LTC-3PN-S2

Nominal Ope	en Circuit Voltage, 25°C	3.67 volts
Nominal Wor	king Voltage, 25°C	3.5 volts
Nominal Cap	pacity (350 hr. rate), 25°C	350 mAH
Volume		0.103 cu. in.
Weight		4.6 GMS
Operating Te	mperature	40°C to +95°C

Case Material: 304 Stainless Steel, Hermetically Sealed (case negative polarity) Terminal and Support Pins are .030" dia. (solder tinned)




.70

.30

SPECIFICATIONS LTC-3PN-S4

Nominal Oper	n Circuit Voltage, 25°C	3.67 volts
Nominal Work	king Voltage, 25°C	3.5 volts
Nominal Capa	acity (350 hr. rate), 25°C	350 mAH
Volume		0.103 cu. in.
Weight		4.6 GMS
Operating Tem	nperature	40°C to +95°C

Case Material: 304 Stainless Steel, Hermetically Sealed (case negative polarity) Terminal and Support Pins are .030" dia. (solder tinned)



The specifications on this sheet may be changed by EaglePicher without notice.

EaglePicher™ is a trademark of and Keeper® is a registered trademark of EaglePicher Corporation.

WE CAN DESIGN TO FIT ANY APPLICATION.

Our team of engineers can design any pin configuration required to fit your specialized application. If you don't see a battery configuration you need here, call us and we will begin working on a EPT part number just for you.

Eagle Picher Commercial Power Solutions

Keeper®

3220 Industrial Drive • Joplin, MO 64801 Tel: 1-800-201-0215 • Fax: 417-626-2078

E-mail: solutions@eaglepicher.com • Web site: www.epcompower.com Copyright ©2006 EaglePicher Corporation DISTRIBUTED LOCALLY BY:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Eagle-Picher:

LTC-3PN LTC-3PNS4 LTC-3PN-SM-S2 LTC-3PNS2