

## Specification Sheet

Part Number: 181-00603



High Density Slotted Wall Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, Black, 120ft/Carton

**Article Number**

181-00603

**Type**

SLHD1.5X1.5

**Color**

Black (BK)

**Features & Benefits**

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.
- Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

**Quantity Per**

carton

|   |  |
|---|--|
| <b>Product Description</b>              | HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| <b>Short Description</b>                | High Density Slotted Wall Wiring Duct, 1.5" x 1.5", Non-Adhesive, PVC, Black, 120ft/Carton   |
| <b>Global Part Name</b>                 | SLHD1.5X1.5-PVC-BK   |
| <b>Technical Description</b>            | Non-Adhesive   |
| <b>Length L (Imperial)</b>              | 6.0  |
| <b>Length L (Metric)</b>                | 1.83   |
| <b>Width W (Imperial)</b>               | 1.5  |
| <b>Width W (Metric)</b>                 | 38.1   |
| <b>Height H (Imperial)</b>              | 1.57   |
| <b>Height H (Metric)</b>                | 39.9   |
| <b>Mounting Hole Centers (Imperial)</b> | 2.0  |
| <b>Material</b>                         | Polyvinylchloride (PVC)  |
| <b>Material Shortcut</b>                | PVC  |

|  |  |
|--|--|
| <b>Flammability</b>                    | Self-Extinguishing                               |
| <b>Halogen free</b>                    | No   |
| <b>Operating Temperature (Metric)</b>  | +122°F (+50°C)                                   |
| <b>Reach Complaint(Article 33)</b>     | No   |
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | EN 50085-1:2005 + A1:2013 UL CSA EN 50085-2-3_1A |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Package Quantity(Imperial)</b>      | 120  |
| <b>Package Quantity (Metric)</b>       | 36.58  |
| <b>Customs Number</b>                  | 3925900000                                       |