



### FEATURES:

- Test probes and leads comply with IEC 1010-2-031 requirements
- Probes, alligator clips & spade lugs fit directly onto test leads for test versatility
- Test accessories conveniently store in the tri-fold nylon pouch provided
- Compatible with most Fluke, H.P., Tektronix & Wavetek digital multimeters
- Kit contains one set of black and red items below

### MATERIALS:

Model: 6261: Minipincer to Banana Jack: Body: Nylon Pincer: Beryllium-Copper, Gold Plated

Wire: 18 AWG, 65 x 36 Tinned Copper, Insulation – Silicone, .144" (3.66 mm) O.D.,

Banana Jack Body – Brass, Nickel Plated Insulation – Nylon. **RATINGS:** Category II, 300V 5 Amperes

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

**Model 6275:** Precision Electronic Probe: Right Angle Sheathed Banana Plug: Plug Body: Nickel plated brass. Banana Plug Spring: Nickel Plated Beryllium copper. Insulation: Polypropylene, Fire Retardant. Wire: 24 AWG, silicon rubber .089 (2.26mm) O.D., Tips: Stainless Steel and one full set of replacement tips, see below. **RATINGS:** Operating Temperature; 55° C., Voltage: CAT III 1000V, 3 Amperes

**Model 6041B:** Large Alligator Clip: Body-Steel, Nickel plated, Insulation-Nylon, Color: One Black, One Red, **RATINGS:** Voltage: 1000 VRMS, 10 Amperes

**Model 6153:** Spade Lug w/ Jack: ETP 110 Copper, 1/2 Hard. Finish: Nickel Plated

**Model 6252:** Banana Plug Coupler: Brass, Nickel Plated, Insulation: Nylon, **RATINGS:** CAT III 1000V, 10 Amperes

**Model 6248:** Minigrabber to Banana Jack: Body: Nylon, Hook: Beryllium Copper, Gold Plated, Wire: 18 AWG, Insulation – Silicone, .144", Banana Jack: Body – Brass, Nickel Plated, Insulation – Nylon, **RATINGS:** Category II, 300V, 5 Amperes

**Model 5907A:** Test Lead Straight to Right Angle: Banana Spring: Nickel plated Beryllium Copper, Insulation – Polypropylene, Wire: 48" silicone 18" AWG, Color: One Black, One Red, **RATINGS:** CAT III 1000V, 10 Amperes

**Model 5906A:** Modular Probe with Banana Plug Tip: Probe Body: Nylon, Plug Tip: Brass, Nickel Plated, Spring – Beryllium Copper, Nickel Plated, 4mm Safety Jack: Brass, Nickel Plated, **RATINGS:** CAT III 1000V, 10 Amperes

**Model 5916A:** Medium Alligator Clip: Body-Steel, Nickel Plated, Color: One Black, One Red, **RATINGS:** CAT II 300V, 5 Amperes

**Model 6354:** Set of 5 Replacement Tips for the Model 6275 Probe

### ORDERING INFORMATION: 6340 (Includes a kit of items from above)

Replacement P/N's: Model **6041A:** Ex-Large Alligator Clip Set, Model **5916A:** Medium Alligator Clip Set, Model **6153:** Spade Lug, Model **6248-12-\***: Minigrabber Jack, Model **5906A:** Modular Test Probe Set, Model **5907A:** Test Lead Set Straight to Right Angle, Model **6252:** Coupler Set, Model, **6261-12-\***: Minipincer/Jack, Model **6275:** Precision Electronic Probe Set, Model **6354:** Set of 5 replacement tips 2 each: Plunger tip, gold plated, 1" & 3" stainless steel Straight tips, 3 point crown tip, plunger, and 4 point plunger tip.

\* 0 - Black, 2 - Red Set = 1 Black, 1 Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Pomona:](#)

[6340](#)