

# XS8G12PA140L1

inductive sensor XS8 12x40x26 - plastic -  
Sn4mm - 12..24VDC - cable 5m



## Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS8
Sensor design	Form 12 x 40 x 26
Size	26 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	4 mm
Discrete output function	1 NO
Discrete output type	PNP
Electrical connection	Cable
Cable length	5 m
Wire insulation material	PVC
[Us] rated supply voltage	12...24 V DC
Switching capacity in mA	≤ 100 mA with overload and short-circuit protection
IP degree of protection	IP67 conforming to IEC 60529

## Complementary

Detection face	Lateral
Detector flush mounting acceptance	Non flush mountable
Material	Plastic
[Sd] sensing range	> 2.5...4 mm
Operating zone	0...3.2 mm
Differential travel	3...20% of Sr
Repeat accuracy	≤ 10% of Sr
Output circuit type	DC
Cable composition	3 x 0.34 mm <sup>2</sup>
Status LED	1 LED yellow for output state
Supply voltage limits	10...30 V DC
Switching frequency	≤ 1000 Hz
Voltage drop	≤ 1.8 V at closed state
Current consumption	0...10 mA at no-load
Delay first up	≤ 4 ms
Delay response	≤ 0.5 ms
Delay recovery	≤ 1 ms
Marking	CE
Length	40 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Product certifications	CSA UL
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27
RoHS EUR conformity date	0836
RoHS EUR status	Compliant

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XS8G12PA140L1](#)