



Part Number: 9541

RS232, #24-15c, SR-PVC, O/A Foil, PVC Jkt, CMG

Product Description

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

Technical Specifications

Product Overview

| | |
|------------------------|--------|
| Suitable Applications: | RS-232 |
|------------------------|--------|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 24 | 7x32 | TC - Tinned Copper | 15 |

| | |
|------------------|--------|
| Conductor Count: | 15 |
| Conductor Size: | 24 AWG |

Insulation

| Material | Nominal Wall Thickness |
|--------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.01 in |

Color Chart

| Number | Color |
|--------|--------------|
| 1 | Black |
| 2 | White |
| 3 | Red |
| 4 | Green |
| 5 | Orange |
| 6 | Blue |
| 7 | White/Black |
| 8 | Red/Black |
| 9 | Green/Black |
| 10 | Orange/Black |
| 11 | Blue/Black |
| 12 | Black/White |
| 13 | Red/White |
| 14 | Green/White |
| 15 | Blue/White |

Color Chart 2

| Number |
|--------|
| 13 |

Outer Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|--------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Aluminum/Polyester | Beldfoil® | 100 % | TC - Tinned Copper | 24 | 7x32 mm |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.284 in | 0.032 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 25 Ohm/1000ft | 18 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 30 pF/ft | 55 pF/ft |

Current

| Element | Max. Recommended Current [A] |
|----------------------|------------------------------|
| 10C Temperature Rise | Per conductor @ 25°C: 1.75 A |

| | |
|---------------------|----------------------|
| Current Table Note: | 10C Temperature Rise |
|---------------------|----------------------|

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V RMS |

Temperature Range

| | |
|-----------------------|--------------------------|
| UL Temp Rating: | 80°C (UL AWM Style 2464) |
| Operating Temp Range: | -30°C To +80°C |

Mechanical Characteristics

| | |
|----------------------------------|---------------|
| Bulk Cable Weight: | 52 lbs/1000ft |
| Max Recommended Pulling Tension: | 82.5 lbs |
| Min Bend Radius/Minor Axis: | 3 in |

Standards

| | |
|--------------------------|-------------------|
| NEC Articles: | 800 |
| NEC/(UL) Specification: | CMG |
| CEC/C(UL) Specification: | CMG |
| UL AWM Style: | 2464 (300 V 80°C) |
| CPR Euroclass: | Eca |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|--------------------|
| UL Flammability: | UL1685 FT4 Loading |
| CSA Flammability: | FT4 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

| Item # | Color | Footnote |
|---------------|--------|----------|
| 9541.0030 | Chrome | |
| 9541.00305 | Chrome | |
| 9541.00U152 | Chrome | |
| 9541.00U305 | Chrome | |
| 9541.01152 | Chrome | |
| 9541 060100 | Chrome | |
| 9541 0601000 | Chrome | C |
| 9541 060500 | Chrome | C |
| 9541 0605000 | Chrome | |
| 9541 060U1000 | Chrome | |
| 9541 060U500 | Chrome | |

Footnote: C - CRATE REEL PUT-UP.

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.