





THIS DRAWING IS UNPUBLISHED.
RELEASED FOR PUBLICATION NOV, 2007.
© COPYRIGHT 2007 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

REVISIONS			
LOC	DIST	DESCRIPTION	
P	LTR	DATE	DNW APVD
	A	FIRST ISSUE	
		23NOV2007	JMS FWK


NOTES:
1. ELECTRICAL DATA: CONTACT RESISTANCE: 10 mOhm MAX
INSULATION RESISTANCE: 100 MOhm MIN at 500VDC
CURRENT RATING: 5 AMPS (FOR 3, 4 AND 5 POSITIONS) AND 2 AMPS (FOR 8 POSITIONS)
BREAKDOWN VOLTAGE: 500 VAC MIN PER MINUTE
2. ENVIRONMENTAL: OPERATING TEMPERATURE: -25°C TO +90°C
SEALING REQUIREMENTS: IP67
3. PACKAGING: 107-3334
4. SEAL FOR CABLE OD: Ø4.5mm - Ø6.0mm
5. FOR TECHNICAL DATA REFER TO YOUR LOCAL TYCO ELECTRONICS SALES OFFICE.
6. ALL DIMENSIONS ARE FOR NOMINAL REFERENCE ONLY UNLESS OTHERWISE STATED.




1991124-2
PIN ASSIGNMENTS
FRONT VIEW



1991124-3
PIN ASSIGNMENTS
FRONT VIEW



M12 FIELD SERVICEABLE CONNECTOR, SCREW FIXING RIGHT ANGLE MALE	5	1991124-3
M12 FIELD SERVICEABLE CONNECTOR, SCREW FIXING RIGHT ANGLE MALE	4	1991124-2
DESCRIPTION	NO. OF POS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 23NOV2007 J.SANDWELL CHK 23NOV2007 F.WHEELER-KING APVD 23NOV2007 F.WHEELER-KING PRODUCT SPEC
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED
		0 PLC \pm 1 PLC \pm 2 PLC \pm 3 PLC \pm 4 PLC \pm ANGLES \pm
MATERIAL		APPLICATION SPEC
-		—
FINISH		WEIGHT —
CUSTOMER DRAWING		
SIZE	CAGE CODE	DRAWING NO
A2	00779	C-1991124
RESTRICTED TO	—	
SCALE	NTS	SHEET
1 OF 1	REV A	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1991124-2](#)