



# Product: <u>5502GE</u> ☑

Security & Sound, #22-2c, BC, Shielded, CMR

### **Product Description**

Security & Sound Cable, Riser-CMR, 1-22 AWG stranded bare copper pair with polyolefin insulation and Beldfoil® shield, 2-22 AWG stranded bare copper conductors with insulation, overall PVC jacket with ripcord

### **Technical Specifications**

### **Physical Characteristics (Overall)**

Conductor				
AWG	Stranding	Material	No. of Pai	rs
22	7x30	BC - Bare Copper	1	
Condu	ctor Count:			4

#### Insulation

Material	Nominal Wall Thickness
Polyolefin (PO, PE, PP)	0.007 in

### Color Chart

Color		
Black & Red (shielded pair)		
White		
Green		

#### Inner Shield Material

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Таре	Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	24

### **Outer Shield Material**

Material No Shield

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.152 in	0.017 in

### **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR 16.4 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
37 pF/ft	66.5 pF/ft

#### Inductance

Nominal Inductance

### 0.16 µH/ft

#### Current

Max. Recommended Current [A]
2.2 Amps per conductor @ 25°C A

#### Voltage

UL Voltage Rating 300 V RMS

### **Temperature Range**

Operating Temp Range:	-20°C To +75°C

### **Mechanical Characteristics**

Bulk Cable Weight:	18.2 lbs/1000ft
Max Recommended Pulling Tension:	42 lbs
Min Bend Radius/Minor Axis:	1.5 in

### Standards

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG

### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1666 Riser
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6502GE

### Part Number

## Variants

ltem #	Color	UPC
5502GE 010U1000	Black	612825163350
5502GE 001U1000	Brown	612825163329
5502GE 0081000	Gray	612825163343
5502GE 008U1000	Gray	612825163336

#### History

Update and Revision:

Revision Number: 0.219 Revision Date: 04-02-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.