


寸法公差は±0.20
(TOLERANCE: ±0.2)
パネル取付穴
(DIMENSION OF PANEL)



- NOTES:
- 1, APPLIED CONTACT P/N: 170359, 170360, 170361, 170362
 - 2, MATING CONN: PLUG HOUSING P/N 172339
 - △ PANEL THICKNESS: 0.8 ~ 2.0 mm
 - 4, PRESS DIRECTION OF PANEL MUST BE SAME AS HOUSING INSERTED DIRECTION.
 - 5, INSTRUCTION SHEET: IS-105J
 - 6, PRODUCT SPEC: 108-5151
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

- 注:
1. 使用端子型番は 170359, 170360, 170361, 170362
 2. 嵌合相手ハウジング型番は 172339
 - △ 適用パネル厚 0.8 ~ 20 mm
 4. 取付穴打抜方向とハウジングの挿入方向は同じとする
 5. 取扱説明書: IS-105J
 6. 適用製品仕様書: 108-5151

OBSOLETE	黄 (YELLOW)	1 - 172331 - 4
	黒 (BLACK)	1 - 172331 - 9
	青 (BLUE)	1 - 172331 - 6
	緑 (GREEN)	1 - 172331 - 5
	赤 (RED)	1 - 172331 - 2
	自然色 (NATURAL)	172331 - 1
	色 (COLOR)	型番 (P/N)

材料 (MATERIAL) 6/6 ナイロン (UL94V-2) (NYLON 6/6 UL94V-2)	一般公差 TOLERANCE ± 0.3 EXCEPT ± 1° AS NOTED	名称 (NAME) MINI-UNIVERSAL MATE-N-LOK CONN. CAP HOUSING 6Pos. (UL94V-2) 6 極 ミニユニバーサルメイトンロックコネクタ キャップハウジング (UL94V-2)	
仕上 (FINISH) 色: 表参照 HOUSING COLOR : SEE TABLE	DR. R. YUASA 4/20/11 CHK. J. TANIPAWAN DE. 4/21/11 APP.	SIZE B LOC J 番号 (NO.) C-172331	尺度 (SCALE) 2:1 REV. A3 SHEET

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-172331-2](#)