



**MATERIALS:**

- OVERMOLD - PVC, BLACK
- CABLE - 2 CONDUCTOR, 28AWG, SPIRAL SHIELDED  
BLACK PVC JACKET
- PLUG - BRASS, NICKEL PLATED

**WIRING**  
 TIP TO WHITE CONDUCTOR  
 RING TO RED CONDUCTOR  
 SLEEVE TO SHIELD

**S & T**

**NOTES:**

1. PRIMARY UNITS ARE METRIC (MM [INCH]).
2. THIS PRODUCT IS RoHS COMPLIANT.

PART NUMBER	DIMENSION "X"	
	METERS	INCHES
250HR07984X	2 METERS+50mm/-0	79.00+2.00/-0

**CUSTOMER DRAWING**

					★ STAR SYMBOL DENOTES CRITICAL DIMENSION	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					UNLESS OTHERWISE SPECIFIED	SIZE	WIDTH	MULT	LBS/M	TEMPER	
					1. ALL DIMENSIONS IN INCHES -TWO PLACE DECIMALS ±0.01 -THREE PLACE DECIMALS ±0.005 -ANGLES ±1° -ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R.	FINISH		MATERIAL			
					2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002	SPEC No.		SPEC No.			
					3. REMOVE ALL BURRS	FIRST USED ON		SCALE 3:2		<b>Switchcraft®</b>	
A	26298	03-25-08	AH	TJK	DATE DRAWN 03-04-08	BY AH	CHKD AH 03-04-08	APVD BDS 03-04-08	SHEET 1 OF 1		
REV	ECD NUMBER	DATE	BY	APVD	NAME CABLE ASSEMBLY 2.5mm 3 CONDUCTOR ST TO S & T, RoHS					PART No. 250HR__84X	REV A
REVISIONS					DO NOT SCALE DRAWING						



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Switchcraft:](#)

[250HR07984](#)