



PCB DRILLING DETAILS

TECHNICAL SPECIFICATION

HOUSING MATERIAL : THERMOPLASTIC POLYESTER UL94V0; GREY
 HOUSING CAN WITHSTAND EXPOSURE TO LEAD FREE WAVE SOLDERING TEMPERATURE OF 260-265°C FOR STRAIGHT CONNECTORS AS IT IS IN CLASSICAL LEAD WAVE SOLDERING AT 235-250°C
 CONTACT & HARPOON MATERIAL : COPPER ALLOY
 CONTACT PLATING :
 ACTIVE ZONE : Au / GXT™ OVER Ni
 TERMINATION ZONE : Sn (PURE MATT) OVER Ni
 HARPOON PLATING : Sn (PURE MATT) OVER Ni

ELECTRICAL DATA

CURRENT RATING AT 20°C : 15 A
 CURRENT (I MAX) : 2 A
 TEMPERATURE RANGE : -55°C TO +125°C
 CONTACT RESISTANCE : ≤ 20 mΩ
 INSULATION RESISTANCE : ≥ 10⁶ MΩ
 TEST VOLTAGE (rms) : 1000 V

MECHANICAL DATA

INSERTION FORCE PER CONTACT : ≤ 0.94 N
 EXTRACTION FORCE PER CONTACT : ≥ 0.15 N
 REFERENCE SPECIFICATION : DIN 41612 / IEC 603-2

SERIES	8609	3	48	8	3	14	7	5	5	V1LF
ROWS FITTED WITH CONTACTS										
ROW a b c	3			48						
ROW a - c	4			32						
NO. OF CONTACTS										
TYPE OF INSULATOR										
3 ROW FEMALE INSULATOR	8									
METHOD OF MOUNTING										
STANDARD MOUNTING - STYLE C/2	3									
TERMINATION										
STRAIGHT SPILL LONG, L = 4.0+0.7/-0	14									
STRAIGHT SPILL SHORT, L = 2.5+0.7/-0	24									
OPTIONS										
NO OPTION	7									
WITH HARPOONS	H									
PERFORMANCE CLASS										
DIN 41612 CLASS 3	4									
DIN 41612 CLASS 2	5									
DIN 41612 CLASS 1	6									
AS PER MIL C 55302 / JSS 50808	8									
PITCH PER ROW										
2.54 mm	5									
LEAD FREE VERSION	V1LF									

NOTES:
 1. THE "LF" PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-0004.
 2. LEAD FREE OR RoHS DIRECTIVE LABELING TO BE PROVIDED AS PER GS-14-920 FOR LEAD FREE VERSION.
 3. FOR GENERAL CHARACTERISTICS AND RoHS INFORMATION, REFER DRAWING C-8609-0000A.

mat'l. code SEE TECH. SPEC.				surface ISO 1302 ✓ ISO 406 ISO 1101		tolerance tolerances unless otherwise specified		projection mm		product family 8609			
ltr				ecn no		dr		date		title			
A				I08-0171		KR		2008-12-19		DIN STANDARD RECEPTACLE STRAIGHT SPILL DIN 41612 STYLE C/2			
B				ELX-I-010167		MJA		2012-02-02		scale 2:1			
C				ELX-I-30157		MJA		2018-05-11		0°±1°			
										Amphenol FCI			
										dwg no sheet 1 of 1 size			
										C-8609-2140 A3			
										type Product Customer Drawing			
sheet index		revision sheet		C		1							

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[86093488324755V1LF](#) [86094328324755V1LF](#) [86093488314755V1LF](#) [86093488314H55V1LF](#)
[86093488314765V1LF](#) [86094328314755V1LF](#) [86093488314745V1LF](#) [86093488314H65V1LF](#) [86093488324H45V1LF](#)
[86093488324H55V1LF](#) [86093488324H65V1LF](#) [86094328314745V1LF](#) [86094328314765V1LF](#)
[86094328324H55V1LF](#) [86093488324765V1LF](#) [86094328324785V1LF](#) [86093488314785V1LF](#) [86093488324785V1LF](#)
[86094328314785V1LF](#) [86094328314H55V1LF](#)