

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-,-

© COPYRIGHT - TE Connectivity

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
C		REDRAWN W/O CHANGE PER EC 0020-600-94	06/20/94	-	AF
D		REVISED PER ECO-17-017908	07DEC2017	RS	MZ

5/8-24 THREAD

6.73
[0.265]

5/8-24 THREAD

9.91
[.390]

45.59
[1.795]

21.59
[0.850]

6.73 DIA
[.265]

1 ACCEPTS CABLE RANGE FROM 3.81 [.150] TO 6.35 [.250] WHEN USED WITH FLEXIBLE BOOT 207489-1.

207490-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K.FOLTZ 06/20/94		
DIMENSIONS: mm [INCHES]		CHK R.STONE 06/24/94		
		APVD A.FRANTUM 08/09/94		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME CABLE GRIP, INTERNAL SIZE 11, CPC		
0 PLC ± -		PRODUCT SPEC		
1 PLC ± -		APPLICATION SPEC		
2 PLC ± 0.13 [.005]		SIZE A3		
3 PLC ± -		CAGE CODE 00779		
4 PLC ± -		DRAWING NO C-207490		
ANGLES ± -		RESTRICTED TO		
FINISH		-		
MATERIAL THERMOPLASTIC, COLOR: BLACK		WEIGHT -		
		CUSTOMER DRAWING		
		SCALE 2:1		SHEET 1 OF 1
				REV D

1470-19 (1/15)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[207490-1](#)