


Base strip - GSTB 3/ 3-G-7,62 - 1750168

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 20 A, Number of positions: 3, Pitch: 7.62 mm, Color: green, Contact surface: Tin, Mounting: Wave soldering



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 028268
Weight per Piece (excluding packing)	2.61 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Pitch	7.62 mm
Pin dimensions	1 x 0,8 mm
Hole diameter	1.3 mm

General

Range of articles	GSTB 3
Rated voltage (III/3)	500 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	20 A
Color	green
Stripping length	8 mm
Number of positions	3

Standards and Regulations

Connection in acc. with standard	EN-VDE
	UL

Base strip - GSTB 3/ 3-G-7,62 - 1750168

Classifications

eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

Approvals

Approvals

Approvals

UL Recognized / EAC


Ex Approvals

Approvals submitted

Approval details

Base strip - GSTB 3/ 3-G-7,62 - 1750168

Approvals

UL Recognized 		
	B	D
Nominal current I _N	10 A	10 A
Nominal voltage U _N	250 V	300 V

EAC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1750168](#)