


# High Power Thin Film Wraparound Chip Resistor



## ADDITIONAL RESOURCES



PHP series chip resistors are designed with enlarged backside terminations to reduce the thermal resistance between the topside resistor layer and the solder joint on the end users circuit board.

Actual power handling capability is limited by the end user mounting process. As with any high power chip resistor the ability to remove the generated heat is critical to the overall performance of the device.

## FEATURES

- High purity ceramic substrate
- Power rating to 2.5 W
- Resistance range 10  $\Omega$  to 30.1 k $\Omega$
- Resistor tolerance to  $\pm 0.1$  %
- TCR to  $\pm 25$  ppm/ $^{\circ}\text{C}$
- Flame resistant UL 94 V-0

## APPLICATIONS

- Power supplies
- Power switching
- Braking system
- Test and measurement equipment
- Motor deflection circuits

## TYPICAL PERFORMANCE

|      | ABSOLUTE |
|------|----------|
| TCR  | 25       |
| TOL. | 0.1      |


| STANDARD ELECTRICAL SPECIFICATIONS |   |   |
|------------------------------------|---|---|
| TEST                               | SPECIFICATIONS  | CONDITIONS  |
| Material                           | Nichrome  | -   |
| Resistance Range                   | 10 $\Omega$ to 30.1 k $\Omega$  | -   |
| TCR: Absolute                      | 25 ppm/ $^{\circ}\text{C}$ , 50 ppm/ $^{\circ}\text{C}$ (standard) and, 100 ppm/ $^{\circ}\text{C}$ | -55 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$ |
| Tolerance: Absolute                | 0.1 %, 0.5 %, 1.0 % and, 5.0 %  | +25 $^{\circ}\text{C}$                            |
| Power Rating: Resistor             | 0.375 W - 2.5 W <sup>(1)</sup>  | Maximum at +70 $^{\circ}\text{C}$                 |
| Stability: Absolute                | $\Delta R$ 0.1 %  | 2000 h at +70 $^{\circ}\text{C}$                  |
| Stability: Ratio                   | Not applicable  | -   |
| Voltage Coefficient                | < 0.1 ppm/V   | -   |
| Working Voltage                    | 75 V to 200 V   | -   |
| Operating Temperature Range        | -55 $^{\circ}\text{C}$ to +155 $^{\circ}\text{C}$   | -   |
| Storage Temperature Range          | -55 $^{\circ}\text{C}$ to +155 $^{\circ}\text{C}$   | -   |
| Noise                              | < -30 dB  | -   |
| Shelf Life Stability: Absolute     | $\pm 0.01$ %  | 1 year at +25 $^{\circ}\text{C}$                  |

| COMPONENT RATINGS |                     |                     |                               |
|-------------------|---------------------|---------------------|-------------------------------|
| CASE SIZE         | POWER RATING (mW)   | WORKING VOLTAGE (V) | RESISTANCE RANGE ( $\Omega$ ) |
| 0603              | 375 <sup>(1)</sup>  | 75                  | 10 to 30.1K                   |
| 0805              | 625 <sup>(1)</sup>  | 100                 | 10 to 30.1K                   |
| 1206              | 1000 <sup>(1)</sup> | 200                 | 10 to 30.1K                   |
| 2512              | 2500 <sup>(1)</sup> | 200                 | 10 to 30.1K                   |





### Note

<sup>(1)</sup> Dependent on component mounting by user


| ENVIRONMENTAL TESTS (Vishay Performance vs. MIL-PRF-55342 Requirements) |   |                                  |
|---|---|----------------------------------|
| ENVIRONMENTAL TEST  | LIMITS MIL-PRF-55342 CHARACTERISTIC "E" | TYPICAL VISHAY PERFORMANCE       |
| Resistance Temperature Characteristic                                   | $\pm 25$ ppm/ $^{\circ}\text{C}$        | $\pm 15$ ppm/ $^{\circ}\text{C}$ |
| Maximum Ambient Temperature at Rated Wattage                            | +70 $^{\circ}\text{C}$                  | +70 $^{\circ}\text{C}$           |
| Maximum Ambient Temperature at Power Derating                           | +150 $^{\circ}\text{C}$                 | +150 $^{\circ}\text{C}$          |
| Thermal Shock   | $\pm 0.1$ %                             | $\pm 0.04$ %                     |
| Low Temperature Operation   | $\pm 0.1$ %                             | $\pm 0.001$ %                    |
| Short Time Overload   | $\pm 0.1$ %                             | $\pm 0.003$ %                    |
| High Temperature Exposure   | $\pm 0.1$ %                             | $\pm 0.030$ %                    |
| Resistance to Soldering Heat  | $\pm 0.2$ %                             | $\pm 0.007$ %                    |
| Moisture Resistance   | $\pm 0.2$ %                             | $\pm 0.002$ %                    |
| Life at +70 $^{\circ}\text{C}$ for 2000 h                               | $\pm 0.5$ %                             | $\pm 0.100$ %                    |

**DIMENSIONS** in inches



| CASE SIZE | LENGTH                  | WIDTH<br>W ( $\pm 0.005$ ) | THICKNESS<br>MIN./MAX. | TOP PAD<br>D ( $\pm 0.005$ ) | BOTTOM PAD<br>E ( $\pm 0.005$ ) |
|-----------|-------------------------|----------------------------|------------------------|------------------------------|---------------------------------|
| 0603      | $0.064 \pm 0.006$       | 0.032                      | 0.020 max.             | 0.012                        | 0.021                           |
| 0805      | $0.080 \pm 0.006$       | 0.050                      | 0.015/0.033            | 0.016                        | 0.025                           |
| 1206      | $0.126 \pm 0.008$       | 0.063                      | 0.015/0.033            | $0.020 + 0.005/- 0.010$      | 0.040                           |
| 2512      | $0.259 + 0.009/- 0.015$ | 0.124                      | 0.015/0.033            | 0.02                         | 0.050                           |

**LAND PATTERN DIMENSIONS** in inches

**STANDARD MATERIAL SPECIFICATIONS**


|                               |   |
|-------------------------------|---|
| Resistive Element             | Nichrome  |
| Substrate Material            | Alumina ( $Al_2O_3$ )   |
| Terminations (Tin/Lead)       | Tin/lead solder over nickel barrier                             |
| Terminations (Lead (Pb)-free) | Tin/silver/copper (Sn96.5Ag3.0Cu0.5) solder over nickel barrier |

**PHP CHIP TEMP. VS. APPLIED POWER**

**Note**


- Chip surface temperature measured using FLIR SC645 thermal imaging system with an approximate test card surface temperature of 85 °C

**PHP CHIP TEMP. VS. APPLIED POWER**

**Note**

- Chip surface temperature measured using FLIR SC645 thermal imaging system with an approximate test card surface temperature of 85 °C

**PHP CHIP TEMP. VS. APPLIED POWER**

**Notes**


- Chip surface temperature measured using FLIR A40 thermal imaging system with an approximate test card surface temperature of 25 °C
- Thermal imaging was conducted under ambient conditions resulting in a steady state test card surface temperature of 85 °C over the full range of power levels
- Thermal imaging and load life testing was conducted mounting one device to 2" x 3" test cards with 2.5 mil copper plating on both surfaces. Thermal vias on 120 mil centers were utilized for heat transfer between surfaces of the test card

**PHP CHIP TEMP. VS. APPLIED POWER**

**Notes**


- Chip surface temperature measured using FLIR A40 thermal imaging system with an approximate test card surface temperature of 25 °C

| Case Size        | 2512       | 2512        | 2512        |
|------------------|------------|-------------|-------------|
| Resistance Value | Up to 10 Ω | Up to 10 kΩ | Up to 30 kΩ |
| Temperature      | Power (W)  |             |             |
| 70               | 2.44       | 1.81        | 1.87        |
| 150              | 6.82       | 4.89        | 5.19        |
| 200              | 9.33       | 6.63        | 7.09        |

## SINGLE PULSE CURVES



## DERATING CURVE



## GLOBAL PART NUMBER INFORMATION

| GLOBAL MODEL | SUBSTRATE          | CASE SIZE  | TCR  | RESISTANCE   | TOLERANCE  | TERMINATION  | PACKAGING  |
|--------------|--------------------|--|--|--|--|--|--|
| <b>PHP</b>   | <b>0</b> = alumina | <b>0603</b><br><b>0805</b><br><b>1206</b><br><b>2512</b> | <b>E</b> =<br>± 25 ppm/°C<br><b>H</b> =<br>± 50 ppm/°C<br><b>K</b> =<br>± 100 ppm/°C | The first 3 digits are significant figures and the last digit specifies the number of zeros to follow. "R" designates the decimal point.<br><br>Example:<br>10R0 = 10 Ω<br>1000 = 100 Ω<br>1001 = 1 kΩ | <b>B</b> = ± 0.1 %<br><b>D</b> = ± 0.5 %<br><b>F</b> = ± 1.0 %<br><b>G</b> = ± 2.0 %<br><b>J</b> = ± 5.0 % | <b>B</b> = wraparound Sn/Pb solder w/nickel barrier<br><br><b>S</b> = wraparound lead (Pb)-free solder SAC-305 RoHS-compliant - e1 | <b>BS</b> = BULK<br>100 min., 1 mult.<br><b>WS</b> = WAFFLE<br>100 min., 1 mult.<br><b>WI</b> = WAFFLE (item single lot date code)<br>100 min., 1 mult.<br><br>TAPE AND REEL<br><b>T1</b> = 1000 min., 1000 mult.<br><b>T3</b> = 300 min., 300 mult.<br><b>T5</b> = 500 min., 500 mult.<br><b>TF</b> = full reel<br><b>TS</b> = 100 min., 1 mult.<br><b>TI</b> = 100 min., 1 mult. (item single lot date code)<br><b>TP</b> = 100 min., 1 mult. (package unit single lot date) |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.