THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION - ,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	REVISED PER ECO-14-000066	27JUN2014	NK	MM



DETAIL Z
POST DETAIL TYP
2 POST MINIMUM
SCALE 10:1



RECOMMENDED HOLE LAYOUT

		PLATING	HOLD-DOWN POST CONFIG LOCATIONS	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
OBSOLETE	5		1,2,3,4,37,38,39,40	3.984	3.900	39	40	7-104431-7
	5		1,2,3,4,32,33,34,35	3.484	3.400	34	35	7-104431-6
	5		1,2,3,4,27,28,29,30	2.984	2.900	29	30	7-104431-5
	5		1,2,3,4,23,24,25,26	2.584	2.500	25	26	7-104431-4
	5		1,2,3,4,22,23,24,25	2.484	2.400	24	25	7-104431-3
	5		1,2,3,4,21,22,23,24	2.384	2.300	23	24	7-104431-2
	5		1,2,3,4,20,21,22,23	2.284	2.200	22	23	7-104431-1
	5		1,2,3,4,19,20,21,22	2.184	2.100	21	22	7-104431-0
	5		1,2,3,4,18,19,20,21	2.084	2.000	20	21	6-104431-9
	5		1,2,3,4,17,18,19,20	1.984	1.900	19	20	6-104431-8
	5		1,2,3,4,16,17,18,19	1.884	1.800	18	19	6-104431-7
	5		1,2,3,4,15,16,17,18	1.784	1.700	17	18	6-104431-6
	5		1,2,3,4,14,15,16,17	1.684	1.600	16	17	6-104431-5
	5		1,2,3,4,13,14,15,16	1.584	1.500	15	16	6-104431-4
	5		1,2,3,4,12,13,14,15	1.484	1.400	14	15	6-104431-3
	5		1,2,3,4,11,12,13,14	1.384	1.300	13	14	6-104431-2
OBSOLETE	5		1,2,3,4,10,11,12,13	1.284	1.200	12	13	6-104431-1
	5		1,2,3,4,9,10,11,12	1.184	1.100	11	12	6-104431-0
	5		1,2,3,4,8,9,10,11	1.084	1.000	10	11	5-104431-9
	5		1,2,3,4,7,8,9,10	.984	.900	9	10	5-104431-8
	5		1,2,3,4,6,7,8,9	.884	.800	8	9	5-104431-7
	5		1,2,3,4,5,6,7,8	.784	.700	7	8	5-104431-6
	5		1,2,3,4,5,6,7	.684	.600	6	7	5-104431-5
	5		1,2,3,4,5,6	.584	.500	5	6	5-104431-4
	5		1,2,3,4,5	.484	.400	4	5	5-104431-3
	5		1,2,3,4	.384	.300	3	4	5-104431-2
	5		1,2,3	.284	.200	2	3	5-104431-1
	4		1,2,3,4,37,38,39,40	3.984	3.900	39	40	2-104431-7
	4		1,2,3,4,32,33,34,35	3.484	3.400	34	35	2-104431-6
	4		1,2,3,4,27,28,29,30	2.984	2.900	29	30	2-104431-5
6	4		1,2,3,4,23,24,25,26	2.584	2.500	25	26	2-104431-4
	4		1,2,3,4,22,23,24,25	2.484	2.400	24	25	2-104431-3
	4		1,2,3,4,21,22,23,24	2.384	2.300	23	24	2-104431-2
	4		1,2,3,4,20,21,22,23	2.284	2.200	22	23	2-104431-1
OBSOLETE	4		1,2,3,4,19,20,21,22	2.184	2.100	21	22	2-104431-0
	4		1,2,3,4,18,19,20,21	2.084	2.000	20	21	1-104431-9
	4		1,2,3,4,17,18,19,20	1.984	1.900	19	20	1-104431-8
	4		1,2,3,4,16,17,18,19	1.884	1.800	18	19	1-104431-7
	4		1,2,3,4,15,16,17,18	1.784	1.700	17	18	1-104431-6
	4		1,2,3,4,14,15,16,17	1.684	1.600	16	17	1-104431-5
	4		1,2,3,4,13,14,15,16	1.584	1.500	15	16	1-104431-4
	4		1,2,3,4,12,13,14,15	1.484	1.400	14	15	1-104431-3
6 SUPERSEDED	4		1,2,3,4,11,12,13,14	1.384	1.300	13	14	1-104431-2
6	4		1,2,3,4,10,11,12,13	1.284	1.200	12	13	1-104431-1
OBSOLETE	4		1,2,3,4,9,10,11,12	1.184	1.100	11	12	1-104431-0
	4		1,2,3,4,8,9,10,11	1.084	1.000	10	11	104431-9
	4		1,2,3,4,7,8,9,10	.984	.900	9	10	104431-8
	4		1,2,3,4,6,7,8,9	.884	.800	8	9	104431-7
6	4		1,2,3,4,5,6,7,8	.784	.700	7	8	104431-6
OBSOLETE	4		1,2,3,4,5,6,7	.684	.600	6	7	104431-5
	4		1,2,3,4,5,6	.584	.500	5	6	104431-4
6 OBSOLETE	4		1,2,3,4,5	.484	.400	4	5	104431-3
	4		1,2,3,4	.384	.300	3	4	104431-2
	4		1,2,3	.284	.200	2	3	104431-1

1. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND THE HOUSING
2. SELECTIVE POSTS ARE FORMED TO PROVIDE CONNECTOR RETENTION TO PC BOARD UNTIL SOLDERED. RETENTION FEATURE IS FOR .055 MINIMUM PC BOARD THICKNESS. SEE DETAIL Z FOR FORM AND TABLE FOR LOCATIONS.
3. BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
4. POSTS: .000100-.000200 MATTE TIN-LEAD, ALL OVER .000050 NICKEL
5. POSTS: .000100-.000200 MATTE TIN, ALL OVER .000050 NICKEL
6. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± .005
4 PLC ± -
ANGLES ± -

MATERIAL
HOUSING: FLAME RETARDANT THERMOPLASTIC COLOR-BLACK
CONTACT: COPPER ALLOY

FINISH
SEE TABLE

DWN H MOLL 28JUN88
CHK R. FEIDT 28JUN88
APVD R. FEIDT 28JUN88
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, .100CL, RT ANGLE, .025 SQ POSTS, WITH HOLD-DOWN CONFIG

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-104431	—

CUSTOMER DRAWING
SCALE 4:1 SHEET 1 OF 1 REV G

4805 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

104431-2