

## 200V to 400VDC Input Full brick DC-DC Converters

### Features

- ◆ Output Voltages from 7.2V to 57V
- ◆ 450W to 600W Output Power
- ◆ Current Share
- ◆ Operation to 100°C Baseplate
- ◆ Wide Adjustable Output Range
- ◆ Parallel Pin
- ◆ High Efficiency - up to 91%



### Key Market Segments & Applications



Specifications			PAF450F280-12	PAF450F280-24	PAF450F280-28	PAF450F280-48
Model			PAF600F280-12	PAF600F280-24	PAF600F280-28	PAF600F280-48
Nominal Output Voltage	VDC		12	24	28	48
Output Current (Max)	450W 600W	A	38 50	19 25	16.5 21.5	9.5 12.5
Max Output Power	450W 600W	W	456 600	456 600	462 602	456 600
Efficiency (Typ)		%	89-90	91	91	91
Input Voltage Range	VDC		200-400VDC			
Output Voltage Accuracy		%	±1			
Output Voltage Adjustment	VDC		7.2 - 14.4	14.4 - 28.8	16.8 - 33.6	28.8 - 57.6
Max Ripple & Noise		mV	120	240	280	480
Max Line Regulation		mV	48	56	56	96
Max Load Regulation		mV	48	56	56	96
Temperature Coefficient		°C	0.02%/°C			
Overcurrent Protection		%	105 - 140%			
Overvoltage Protection		%	125 - 145%			
Signals & Control	-		Remote Sense, Remote On/Off, Parallel Pin, Inverter Good, 11-14V Auxiliary voltage			
Baseplate Temperature	-		-40°C to +100°C Baseplate: (See derating chart)			
Humidity (non condensing)	-		5 - 95% RH Operating, 5 - 95% RH Non Operating			
Cooling	-		Conduction (See Installation Manual for heatsink selection)			
Isolation Voltage	-		Input to Baseplate: 2500VAC (20mA); Input to Output 3000VAC for 1 min.; Output to Baseplate: 500VDC for 1 min			
Shock	-		196.1m/s <sup>2</sup>			
Vibration	-		Non Operating, 10-55Hz (sweep for 1 min.) Amplitude 0.825mm constant (Max 49 m/s <sup>2</sup> ) X,Y,Z 1 hour each			
Safety Agency Approvals	-		UL60950-1, CSA60950-1, EN60950-1, CE LVD			
Weight (Typ)		g	200			
Size (WxHxD)		mm	2.4 x 0.5 x 4.6 (61 x 12.7 x 116.8) See outline drawing			
Warranty		yr	2 years			

Note: See Installation Manual for full details, test methods of parameters and application notes.



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TDK-Lambda:](#)

[PAF600F280-12](#) [PAF600F280-12/T](#) [PAF600F280-24](#) [PAF600F280-24/T](#) [PAF600F280-28](#) [PAF600F280-28/T](#)  
[PAF600F280-48](#) [PAF600F280-48/T](#)