

## RF 15 N - Tactile switch, non-illuminated, gold contacts

### 3.14.100.601/0000

For keycaps, refer to RK 90 system design.



#### General information

|                      |          |
|----------------------|----------|
| Recommended key grid | 19.05 mm |
|----------------------|----------|

#### Dimensions

|                |        |
|----------------|--------|
| Length         | 15 mm  |
| Width          | 15 mm  |
| Overall height | 6.2 mm |

#### Mechanical design

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Mounting            | soldering in PCB                                     |
| Terminals           | THT                                                  |
| Contact system      | snap-action contact                                  |
| Contact arrangement | 1 NO                                                 |
| Contact materials   | Au                                                   |
| Illumination        | external 3 mm LED possible if height more than 12 mm |

#### Mechanical characteristics

|                      |                               |
|----------------------|-------------------------------|
| Operating force max. | 2.9 <sup>+0.6</sup> N         |
| Switching travel     | 0.5 <sup>+0.2</sup> mm        |
| Robustness max.      | 100 with through-plated PCB N |

#### Electrical characteristics

|                                  |                         |
|----------------------------------|-------------------------|
| Rated voltage min.               | Au: 0.02 V, Ag: 3 V     |
| Rated voltage max.               | 35 V                    |
| Rated current min.               | Au: 0.01 mA, Ag: 0.1 mA |
| Rated current max.               | Au: 100 mA, Ag: 250 mA  |
| Rated power max. (ohmic load)    | Au: 2 W, Ag: 12.5 W     |
| Contact resistance when new max. | 100 mΩ                  |
| Insulation resistance            | 10 <sup>9</sup> Ω       |

#### Other specifications

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Ambient temp. operating min.           | -25 °C                                   |
| Ambient temp. operating max.           | +70 °C                                   |
| Storage temperature max. (in tube)     | +50 °C                                   |
| Environmental resistance               | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Operating life min. (operations)       | 1,000,000 cycle                          |
| Solderability / solder heat resistance | according to DIN EN 60068-2-20           |
| Wave soldering                         | 260 °C max.                              |
| Manual soldering                       | 350 °C / 5 sec. max.                     |


---

|                |     |
|----------------|-----|
| ROHS compliant | yes |
|----------------|-----|

---

|                 |     |
|-----------------|-----|
| REACH compliant | yes |
|-----------------|-----|

---



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

RAFI:

[3.14.100.601/0000](#)