



Part Number: 83010

Lead Wire, #16 Str SPC, TFE Ins, AWM 1371 105C TYPE E

Product Description

High Temp Plastic Lead Wire, 16AWG (19x29) Silver Plated Copper, TFE Insulation, AWM 1371 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
16	19x29	SCC - Silver-coated Copp	per 1
Conductor Count:		1	
Condu	uctor Size:	1	6 AWG

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	0.076 in	0.01 in

Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.077 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 4 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire)	Mil-Std-975M Table 3.16 (single wire): 13 amps

Voltage

Description	Voltage Rating [V]
Mil-W-16878/4	600 V RMS Mil-W-16878/4

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-70°C To +200°C

Mechanical Characteristics

	Bulk Cable Weight:	10 lbs/1000ft	
--	--------------------	---------------	--

Standards

UL AWM Style:	1371
Military Specification:	NEMA HP3, MIL-W-16878/4 (Except For Stranding)

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No			
(, .				

Part Number

Variants

Item #	Color	Footnote
83010 010100	Black	
83010 0101000	Black	SW
83010 010500	Black	SW
83010 006100	Blue, Light	
83010 0061000	Blue, Light	SW
83010 006500	Blue, Light	SW
83010 001100	Brown	
83010 0011000	Brown	SWZ
83010 001500	Brown	SW
83010 008100	Gray	
83010 008500	Gray	SW
83010 005100	Green, Dark	
83010 0051000	Green, Dark	SW
83010 005500	Green, Dark	SW
83010 003100	Orange	
83010 003500	Orange	SW
83010 002100	Red	
83010 0021000	Red	SW
83010 002500	Red	SW
83010 007100	Violet	
83010 007500	Violet	SW
83010 009100	White	
83010 0091000	White	SW
83010 009500	White	SW
83010 004100	Yellow	
83010 0041000	Yellow	SW
83010 004500	Yellow	SW

Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)
Footnote:	W - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

 $\label{eq:All sales} \mbox{ All sales of Belden products are subject to Belden's standard terms and conditions of sale.}$

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.